

index, i, j, k, l, m, n index variables (subscripts)
ident
integer_literal
float_literal
char_literal
string_literal
infix_symbol
prefix_symbol
location, l store locations (not in the source syntax)
lowercase_ident
capitalized_ident

<i>value-name</i> , <i>x</i>	::=		
		<i>lowercase-ident</i>	
		(<i>operator-name</i>)	
<i>operator-name</i>	::=		
		<i>prefix-symbol</i>	
		<i>infix-op</i>	
<i>infix-op</i>	::=		
		<i>infix-symbol</i>	
		*	[L]
		=	[L]
		:=	[L]
<i>constr-name</i> , <i>C</i>	::=		
		<i>capitalized-ident</i>	
<i>typeconstr-name</i> , <i>tcn</i>	::=		
		<i>lowercase-ident</i>	
<i>field-name</i> , <i>fn</i>	::=		
		<i>lowercase-ident</i>	[d]
<i>value-path</i>	::=		
		<i>value-name</i>	
<i>constr</i>	::=	constructors: named, and built-in (including exceptions)	
		<i>constr-name</i>	
		Invalid_argument	[L]
		Not_found	[L]
		Assert_failure	[L]
		Match_failure	[L]
		Division_by_zero	[L]

	None	[L]
	Some	[L]
<i>typeconstr</i>	$::=$	type constructors: named, and built-in
	<i>typeconstr-name</i>	
	int	[L]
	char	[L]
	string	[L]
	float	[L]
	bool	[L]
	unit	[L]
	exn	[L]
	list	[L]
	option	[L]
	ref	[L]
<i>field</i>	$::=$	
	<i>field-name</i>	[d]
<i>idx, num</i>	$::=$	index arithmetic for the type system's deBruijn type variable representation
	<i>m</i>	[I]
	<i>idx₁ + idx₂</i>	[I]
	<i>(num)</i>	S [I]
σ^T	$::=$	multiple substitutions of types for type variables
	$\{\alpha_1 \leftarrow \text{typexpr}_1, \dots, \alpha_n \leftarrow \text{typexpr}_n\}$	[I]
	shift <i>num num' σ^T</i>	M [I]
		shift the indices in the types in σ^T by <i>num</i> , ignoring indices lower than <i>num'</i>
<i>typexpr, t</i>	$::=$	
	α	
	$< \text{idx}, \text{num} >$	[I]
		de Bruijn representation of type variables. <i>num</i> allows each binder (i.e., a polymorphic let) to introduce an arbitrary number of binders

	$\begin{array}{l} - \\ (\textit{typexpr}) \\ \textit{typexpr}_1 \rightarrow \textit{typexpr}_2 \\ \textit{typexpr}_1 * \dots * \textit{typexpr}_n \\ \textit{typeconstr} \end{array}$	S
	in the theorem prover models we use a uniform representation for 0-, 1-, and n-ary type constructor applications	
	$\begin{array}{l} \textit{typexpr} \textit{typeconstr} \\ (\textit{typexpr}_1, \dots, \textit{typexpr}_n) \textit{typeconstr} \\ \textbf{shift} \textit{num} \textit{num}' \textit{typexpr} \\ \quad \text{shifts as in } \sigma^T \text{ above} \\ t_1 \rightarrow \dots \rightarrow t_n \rightarrow t \\ \sigma^T \textit{typexpr} \end{array}$	S M [I] M [I]
	apply the substitution	
$\textit{src_typexpr}, \textit{src_t}$	$::=$	types that can appear in source programs
	α	
	$\begin{array}{l} - \\ (\textit{src_typexpr}) \\ \textit{src_typexpr}_1 \rightarrow \textit{src_typexpr}_2 \\ \textit{src_typexpr}_1 * \dots * \textit{src_typexpr}_n \\ \textit{typeconstr} \\ \textit{src_typexpr} \textit{typeconstr} \\ (\textit{src_typexpr}_1, \dots, \textit{src_typexpr}_n) \textit{typeconstr} \\ \textbf{shift} \textit{num} \textit{num}' \textit{src_typexpr} \end{array}$	
α	$::=$	
	$'\textit{ident}$	
$\textit{typescheme}, \textit{ts}$	$::=$	
	$\begin{array}{l} \forall \textit{typexpr} \\ \textbf{shift} \textit{num} \textit{num}' \textit{typescheme} \end{array}$	M [I] M [I]
	shifts as in σ^T above	

<i>n</i>	::=		integer mathematical expressions, used to implement primitive operations and
<i>integer_literal</i>			
<i>(n)</i>	M	[I]	
<i>n</i> ₁ + <i>n</i> ₂	M	[I]	
<i>n</i> ₁ - <i>n</i> ₂	M	[I]	
<i>n</i> ₁ * <i>n</i> ₂	M	[I]	
<i>n</i> ₁ / <i>n</i> ₂	M	[I]	
<i>constant</i>	::=		
<i>n</i>		[L]	
<i>float_literal</i>		[L]	
<i>char_literal</i>		[L]	
<i>string_literal</i>		[L]	
equal_error_string	M	[L]	
The string constant "equal: functional value"			
<i>constr</i>		[L]	
false		[L]	
true		[L]	
[]		[L]	
()		[L]	
<i>pattern, pat</i>	::=		
<i>value_name</i>	xs = <i>value_name</i>		
-	xs = {}		
<i>constant</i>	xs = {}		
<i>pattern as value_name</i>	xs = xs(<i>pattern</i>) ∪ <i>value_name</i>		
(<i>pattern</i>)	S		
(<i>pattern</i> : <i>typexpr</i>)	xs = xs(<i>pattern</i>)		
<i>pattern</i> ₁ <i>pattern</i> ₂	xs = xs(<i>pattern</i> ₁)		
<i>constr</i> (<i>pattern</i> ₁ , ..., <i>pattern</i> _n)	xs = xs(<i>pattern</i> ₁ ... <i>pattern</i> _n)		
<i>constr</i> -	xs = {}		
<i>pattern</i> ₁ , ..., <i>pattern</i> _n	xs = xs(<i>pattern</i> ₁ ... <i>pattern</i> _n)		
{ <i>field</i> ₁ = <i>pattern</i> ₁ ; ...; <i>field</i> _n = <i>pattern</i> _n }	xs = xs(<i>pattern</i> ₁ ... <i>pattern</i> _n)	[d]	

	$[pattern_1; \dots; pattern_n]$	S	[L]
	$pattern_1 :: pattern_2$	$\text{xs} = \text{xs}(pattern_1) \cup \text{xs}(pattern_2)$	[L]
<i>unary-prim</i>	::=		primitive functions with one argument
	raise		[L I]
	not		[L I]
	\sim		[L I]
	ref		[L I]
	!		[L I]
<i>binary-prim</i>	::=		primitive functions with two arguments
	=		[L I]
	+		[L I]
	-		[L I]
	*		[L I]
	/		[L I]
	$::=$		[L I]
<i>expr, e</i>	::=		
	(%prim <i>unary-prim</i>)		[L I]
	a unary primitive function value		
	(%prim <i>binary-prim</i>)		[L I]
	a binary primitive function value		
	<i>value-name</i>		
	<i>constant</i>		
	(<i>expr</i>)	S	
	begin <i>expr</i> end	S	
	(<i>expr</i> : <i>typeexpr</i>)		
	<i>expr</i> ₁ , ..., <i>expr</i> _n		
	<i>constr</i> (<i>expr</i> ₁ , .., <i>expr</i> _n)		
	potentially empty constructors to work around ott parser restriction		
	<i>expr</i> ₁ :: <i>expr</i> ₂		[L]
	[<i>expr</i> ₁ ; ...; <i>expr</i> _n]	S	[L]

<code>{field₁ = expr₁; ...; field_n = expr_n}</code>		[d]
<code>{expr with field₁ = expr₁; ...; field_n = expr_n}</code>		[d]
<code>expr₁ expr₂</code>	S	
<code>prefix-symbol expr</code>	S	
<code>expr₁ infix-op expr₂</code>	S	
<code>expr₁&&expr₂</code>		[L]
<code>AND (expr₁&&..&&expr_n)</code>	M	[L I]
a delimited “and” operator with a list of arguments		
<code>expr₁ expr₂</code>		[L]
<code>expr.field</code>		[d]
<code>if expr₀ then expr₁</code>	S	
<code>if expr₀ then expr₁ else expr₂</code>		
<code>while expr₁ do expr₂ done</code>		
<code>for x = expr₁ [down]to expr₂ do expr₃ done</code>	bind x in expr ₃	
<code>expr₁; expr₂</code>		
<code>match expr with pattern-matching</code>		
<code>function pattern-matching</code>		
<code>fun pattern₁ ... pattern_n → expr</code>	S	
<code>try expr with pattern-matching</code>		
<code>let let-binding in expr</code>	bind xs(let-binding) in expr	
omitting multiple bindings, i.e. and		
<code>let rec letrec-bindings in expr</code>	bind xs(letrec-bindings) in letrec-bindings bind xs(letrec-bindings) in expr	
<code>assert expr</code>		
<code>location</code>		
<code>{substs-x}expr</code>	M	[I]
substitution of expressions for variables		[I]
<code>remv_tyvar expr</code>	M	[I]
replace the type variables in an expression’s type annotations with _		
<code>[down]to</code>	::=	
	to	
	downto	

substs_x

::=

- | *value-name*₁ ← *expr*₁, .., *value-name*_n ← *expr*_n
- | *substs_x*₁ @ .. @ *substs_x*_n

M

substitutions of expressions for var
[I]
[I]

pattern-matching, pm

::=

- | *pat-exp*₁ | ... | *pat-exp*_n
- | *pat-exp*₁ | ... | *pat-exp*_n

S

pat-exp

::=

- | *pattern* → *expr*

bind xs(*pattern*) in *expr*

let-binding

::=

- | *pattern* = *expr*
- | *value-name* *pattern*₁ .. *pattern*_n = *expr*
- | *value-name* *pattern*₁ .. *pattern*_n : *typeexpr* = *expr*
- | { $\alpha_1 \leftarrow \text{typeexpr}_1, \dots, \alpha_n \leftarrow \text{typeexpr}_n$ } *let-binding*
substitution of types for type variables

xs = xs(*pattern*)
S
S
M

letrec-bindings

::=

- | *letrec-binding*₁ and .. and *letrec-binding*_n
- | { $\alpha_1 \leftarrow \text{typeexpr}_1, \dots, \alpha_n \leftarrow \text{typeexpr}_n$ } *letrec-bindings*
substitution of types for type variables

xs = xs(*letrec-binding*₁..*letrec-binding*_n)
M

letrec-binding

::=

- | *value-name* = **function** *pattern-matching*
- | *value-name* = **fun** *pattern* *pattern*₁ .. *pattern*_n → *expr*
- | *value-name* *pattern* *pattern*₁ .. *pattern*_n = *expr*
- | *value-name* *pattern* *pattern*₁ .. *pattern*_n : *typeexpr* = *expr*

xs = *value-name*
S
S
S

type-definition

::=

- | **type** *typedef*₁ and .. and *typedef*_n
potentially empty definitions to work around Ott parser restrictions

type_names = type_names(*typedef*₁..*typedef*_n) [d]
constr_names = constr_names(*typedef*₁..*typedef*_n)

<i>typedef</i>	::=			
		<i>type_params_opt typeconstr_name type_information</i>	bind typevars(<i>type_params_opt</i>) in <i>type_information</i> type_names = <i>typeconstr_name</i> constr_names = constr_names(<i>type_information</i>)	[d]
<i>type_information</i>	::=			
		<i>type_equation</i>	constr_names = {} field_names = {}	[d]
		<i>type_representation</i>	constr_names = constr_names(<i>type_representation</i>) field_names = field_names(<i>type_representation</i>)	[d]
<i>type_equation</i>	::=			
		= <i>typexpr</i>		[d]
<i>type_representation</i>	::=			
		= <i>constr_decl</i> ₁ ... <i>constr_decl</i> _n	constr_names = constr_names(<i>constr_decl</i> ₁ ... <i>constr_decl</i> _n)	[d]
		= { <i>field_decl</i> ₁ ; ... ; <i>field_decl</i> _n }	field_names = {} constr_names = {} field_names = field_names(<i>field_decl</i> ₁ ... <i>field_decl</i> _n)	[d]
<i>type_params_opt</i>	::=			
			S	[d]
		in the theorem prover models we use a uniform representation for empty, singleton and multiple type parameters		
		<i>type_param</i>	S	[d]
		(<i>type_param</i> ₁ , ..., <i>type_param</i> _n)	typevars = typevars(<i>type_param</i> ₁ ... <i>type_param</i> _n)	[d]
<i>type_param, tp</i>	::=			
		α	typevars = α	[d]
<i>constr_decl</i>	::=			
		<i>constr_name</i>	constr_names = <i>constr_name</i>	[d]
		<i>constr_name</i> of <i>typexpr</i> ₁ * ... * <i>typexpr</i> _n	constr_names = <i>constr_name</i>	[d]

<i>field_decl</i>	::=		
		<i>field_name</i> : <i>typexpr</i>	<i>field_names</i> = <i>field_name</i>
			[d]
<i>exception_definition</i>	::=		
		exception <i>constr_decl</i>	[d]
<i>definition, d</i>	::=		
		let <i>let_binding</i>	<i>xs</i> = <i>xs(let_binding)</i>
		omitting multiple bindings, i.e. and	[d]
		let rec <i>letrec_bindings</i>	<i>xs</i> = <i>xs(letrec_bindings)</i>
		bind <i>xs(letrec_bindings)</i> in <i>letrec_bindings</i>	[d]
		<i>type_definition</i>	<i>xs</i> = {}
		<i>exception_definition</i>	<i>xs</i> = {}
			[d]
			[d]
<i>definitions, ds</i>	::=		
			[d]
		<i>definition definitions</i>	bind <i>xs(definition)</i> in <i>definitions</i>
		<i>definition</i> ; ; <i>definitions</i>	S
		{ <i>substs_x</i> } <i>definitions</i>	M
		substitution of expressions for variables	[d]
		<i>definitions definition</i>	M
		adding a definition to the end of a sequence	[d]
		<i>definitions</i> ; ; <i>definition</i>	M
			[d]
<i>program</i>	::=		
		<i>definitions</i>	[d]
		(%primraise) <i>expr</i>	[d]
<i>value, v</i>	::=		core value
		(%primunary_prim)	[L I]
		(%primbinary_prim)	[L I]
		<i>binary_prim_app_value value</i>	[I]
		partially applied binary primitive	

	<i>constant</i>	[I]
	<i>(value)</i>	[I]
	<i>value</i> ₁ , ..., <i>value</i> _n	[I]
	<i>constr</i> (<i>value</i> ₁ , .., <i>value</i> _n)	[I]
	<i>value</i> ₁ :: <i>value</i> ₂	[L I]
	[<i>value</i> ₁ ; ...; <i>value</i> _n]	[L I]
	{ <i>field</i> ₁ = <i>value</i> ₁ ; ...; <i>field</i> _n = <i>value</i> _n }	[d I]
	function <i>pattern_matching</i>	[I]
	fun <i>pattern</i> ₁ ... <i>pattern</i> _n → <i>expr</i>	[I]
	<i>location</i>	[I]
<i>binary_prim_app_value</i>	::=	
	(%prim <i>binary_prim</i>)	[I]
<i>definition_value, d_value</i>	::=	
	<i>type_definition</i>	[d I]
	<i>exception_definition</i>	[d I]
<i>definitions_value, ds_value</i>	::=	
		[d I]
	<i>definition_value definitions_value</i>	[d I]
	<i>definition_value</i> ; ; <i>definitions_value</i>	[d I]
<i>non_expansive, nexp</i>	::=	nonexpansive expression (allowed in a polymorphic let)
	(%prim <i>unary_prim</i>)	[I]
	(%prim <i>binary_prim</i>)	[I]
	<i>binary_prim_app_value nexp</i>	[I]
	partially applied binary primitive	
	<i>value_name</i>	[I]
	<i>constant</i>	[I]
	(<i>nexp</i>)	[I]
	(<i>nexp</i> : <i>typexpr</i>)	[I]
	<i>nexp</i> ₁ , ..., <i>nexp</i> _n	[I]

	<i>constr</i> (<i>nexp</i> ₁ , .., <i>nexp</i> _{<i>n</i>})	[I]
	<i>nexp</i> ₁ :: <i>nexp</i> ₂	[I]
	[<i>nexp</i> ₁ ; ..; <i>nexp</i> _{<i>n</i>}]	[L I]
	{ <i>field</i> ₁ = <i>nexp</i> ₁ ; ..; <i>field</i> _{<i>n</i>} = <i>nexp</i> _{<i>n</i>} }	[d I]
	let rec <i>letrec-bindings</i> in <i>nexp</i>	[I]
	function <i>pattern-matching</i>	[I]
	fun <i>pattern</i> ₁ ... <i>pattern</i> _{<i>n</i>} → <i>expr</i>	[I]
	<i>location</i>	[I]
<i>store, st</i>	::=	
	empty	[I]
	<i>store, location</i> ↦ <i>expr</i>	[I]
	<i>store, location</i> ↦ <i>expr, store'</i>	M [I]
<i>kind</i>	::=	
	Type ^{<i>num</i>} → Type	S [I]
	Type	[I]
<i>name</i>	::=	environment lookup key
	TV	[I]
	<i>value-name</i>	[I]
	<i>constr-name</i>	[d I]
	<i>typeconstr-name</i>	[d I]
	<i>field-name</i>	[d I]
	<i>location</i>	[I]
<i>names</i>	::=	
	<i>name</i> ₁ .. <i>name</i> _{<i>n</i>}	[I]
<i>typexprs</i>	::=	
	<i>typexpr</i> ₁ , .., <i>typexpr</i> _{<i>n</i>}	[I]
	shift <i>num num'</i> <i>typexprs</i>	M [I]
	shift the indices in the types in <i>typexprs</i> by <i>num</i> , ignoring indices lower than <i>num'</i>	

<i>environment_binding</i> , EB	$::=$			
		TV		[I]
		type variable		
		<i>value_name</i> : <i>typescheme</i>		[I]
		value binding		
		<i>value_name</i> : <i>typexpr</i>	M	[I]
		value binding with no universal quantifier		
		<i>constr_name</i> of <i>typeconstr</i>		[d I]
		constant constructor		
		<i>constr_name</i> of \forall <i>type_params_opt</i> , (<i>typexprs</i>) : <i>typeconstr</i>	bind typevars(<i>type_params_opt</i>) in <i>typexprs</i>	[d I]
		parameterised constructor		
		<i>field_name</i> : \forall <i>type_params_opt</i> , <i>typeconstr_name</i> \rightarrow <i>typexpr</i>	bind typevars(<i>type_params_opt</i>) in <i>typexpr</i>	[d I]
		field name a record destructor		
		<i>typeconstr_name</i> : <i>kind</i>		[d I]
		type name, bound to a fresh type		
		<i>typeconstr_name</i> : <i>kind</i> { <i>field_name</i> ₁ ; ...; <i>field_name</i> _n }		[d I]
		type name which is a record type definition		
		<i>type_params_opt</i> <i>typeconstr_name</i> = <i>typexpr</i>	bind typevars(<i>type_params_opt</i>) in <i>typexpr</i>	[d I]
		type name which is an abbreviation		
		<i>location</i> : <i>typexpr</i>		[I]
		location (memory cell)		
		(<i>EB</i>)	M	[I]
		shift <i>num num' EB</i>	M	[I]
		shift the indices in the types in <i>EB</i> by <i>num</i> , ignoring indices lower than <i>num'</i>		

<i>environment</i> , E	$::=$			
		empty		[I]
		<i>E, EB</i>		[I]
		<i>EB</i> ₁ , ..., <i>EB</i> _n	M	[I]
		<i>E</i> ₁ @..@ <i>E</i> _n	M	[I]

<i>trans_label</i> , L	$::=$			
				reduction label (denoting a side [I])

<code>ref</code>	$v = location$	[l]
	$!location = v$	[l]
	$location := v$	[l]
	L	M [l]
\xrightarrow{L}	$::=$	
	$\mid \xrightarrow{L}$	[l]
<i>formula</i>	$::=$	
	<i>judgement</i>	
	$formula_1 \dots formula_n$	
	$\dot{n}_1 \leq \dot{n}_2$	
	$\dot{n}_1 > \dot{n}_2$	
	$num_1 < num_2$	
	$E = E'$	
	$expr = expr'$	
	$typexpr = typexpr'$	
	$typescheme = typescheme'$	
	$type_params_opt = type_params_opt'$	
	$letrec_bindings = (letrec_bindings')$	
	$length(tp_1) \dots (tp_n) = m$	
	$length(t_1) \dots (t_n) = num$	
	$length(t_1) \dots (t_n) \leq num$	
	$length(t_1) \dots (t_n) \geq num$	
	$length(pat_1) \dots (pat_n) \geq m$	
	$length(e_1) \dots (e_n) \geq m$	
	$name \notin names$	
	$field_name \text{ in } field_name_1 \dots field_name_n$	[d]
	$type_param \text{ in } type_params_opt$	
	$name_1 \dots name_n \text{ distinct}$	
	$tp_1 \dots tp_n \text{ distinct}$	
	$E \text{ PERMUTES } E'$	
	$fn_1 \dots fn_n \text{ PERMUTES } fn'_1 \dots fn'_m$	[d]

```

|  $fn_1 = e_1 \dots fn_n = e_n$  PERMUTES  $fn'_1 = e'_1 \dots fn'_m = e'_m$       [d]
|  $\neg$ (value matches pattern)
| constant  $\neq$  constant'
| name  $\neq$  name'
| store(location) unallocated
| type_vars(let_binding)  $\triangleright$   $\alpha_1, \dots, \alpha_n$ 
| type_vars(letrec_bindings)  $\triangleright$   $\alpha_1, \dots, \alpha_n$ 

```

<i>terminals</i>	$::=$	prettyprinting specifications
	%prim	
	*	
	\rightarrow	
	\longrightarrow	
	\rightarrow	
	\leftarrow	
	{	
	\leq	
	\equiv	
	\geq	
	\nparallel	
	\forall	
	\triangleright	
	\notin	
	\neq	
	\vdash	
	\mapsto	
	\sim	

<i>JdomEB</i>	$::=$	
	dom (EB) \triangleright name	
	Environment binding domain	

<i>JdomE</i>	$::=$	
--------------	-------	--

	$\mid \text{dom}(E) \triangleright names$	Environment domain
$Jlookup$	$::=$	
	$\mid E \vdash name \triangleright EB$	Environment lookup
$Jidx$	$::=$	
	$\mid E \vdash idx \mathbf{bound}$	Well-formed index
$JTtps_kind$	$::=$	
	$\mid \vdash type_params_opt : kind$	Type parameter kinding
$JTEok$	$::=$	
	$\mid E \vdash \mathbf{ok}$	Environment validity
	$\mid E \vdash typeconstr : kind$	Type constructor kinding
	$\mid E \vdash typescheme : kind$	de Bruijn type scheme well-formedness
	$\mid E \vdash \forall type_params_opt, t : kind$	Named type scheme well-formedness
	$\mid E \vdash typexpr : kind$	Type expression well-formedness
$JTeq$	$::=$	
	$\mid E \vdash typexpr \equiv typexpr'$	Type equivalence
$JTidxsub$	$::=$	
	$\mid \{\{typexpr_1, \dots, typexpr_n\} typexpr' \triangleright typexpr''$	

de Bruin type substitution

$JTinst$::=	
		$E \vdash \text{typexpr} \leq \text{typescheme}$ de Bruijn type scheme instantiation
$JTinst_named$::=	
		$E \vdash \text{typexpr} \leq \forall \text{type_params_opt}, \text{typexpr}'$ Named type scheme instantiation
$JTinst_any$::=	
		$E \vdash \text{typexpr} \leq \text{typexpr}'$ Wildcard type instantiation
$JTval$::=	
		$E \vdash \text{value_name} : \text{typexpr}$ Variable typing
$JTfield$::=	
		$E \vdash \text{field_name} : \text{typexpr} \rightarrow \text{typexpr}'$ Field name typing
$JTconstr_p$::=	
		$E \vdash \text{constr} : \text{typexpr}_1 \dots \text{typexpr}_n \rightarrow \text{typexpr}'$ Non-constant constructor typing
$JTconstr_c$::=	
		$E \vdash \text{constr} : \text{typexpr}$ Constant constructor typing
$JTconst$::=	
		$E \vdash \text{constant} : \text{typexpr}$ Constant typing

$JTpat$::=	
		$\sigma^T \& E \vdash pattern : typexpr \triangleright E'$ Pattern typing and binding collection
$JTuprim$::=	
		$E \vdash unary_prim : typexpr$ Unary primitive typing
$JTbprim$::=	
		$E \vdash binary_prim : typexpr$ Binary primitive typing
JTe	::=	
		$\sigma^T \& E \vdash expr : typexpr$ Expression typing
		$\sigma^T \& E \vdash pattern_matching : typexpr \rightarrow typexpr'$ Pattern matching/expression pair typing
		$\sigma^T \& E \vdash let_binding \triangleright E'$ Let binding typing
		$\sigma^T \& E \vdash letrec_bindings \triangleright E'$ Recursive let binding typing
$JTconstr_decl$::=	
		$type_params_opt typeconstr \vdash constr_decl \triangleright EB$ Variant constructor declaration
$JTfield_decl$::=	
		$type_params_opt typeconstr_name \vdash field_decl \triangleright EB$ Record field declaration
$JTtypedef$::=	
		$\vdash typedef_1 \text{ and } .. \text{ and } typedef_n \triangleright E' \text{ and } E'' \text{ and } E'''$ Type definitions collection

$JTtype_definition$	$::=$	
		$E \vdash type_definition \triangleright E'$ Type definition well-formedness and binding collection
$JTdefinition$	$::=$	
		$E \vdash definition : E'$ Definition typing
$JTdefinitions$	$::=$	
		$E \vdash definitions : E'$ Definition sequence typing
$JTprog$	$::=$	
		$E \vdash program : E'$ Program typing
$JTstore$	$::=$	
		$E \vdash store : E'$ Store typing
$JTtop$	$::=$	
		$E \vdash \langle program, store \rangle$ Top-level typing
$JTLin$	$::=$	
		$\sigma^T \& E \vdash L$ Label-to-environment extraction
$JTLout$	$::=$	
		$\sigma^T \& E \vdash L \triangleright E'$ Label-to-environment extraction
$JmatchP$	$::=$	

	$\vdash \text{expr matches pattern}$	Pattern matching
$Jmatch$	$::=$	
	$\vdash \text{expr matches pattern} \triangleright \{\text{substs_}x\}$	Pattern matching with substitution creation
$Jrecfun$	$::=$	
	$\mid \text{recfun}(\text{letrec_bindings}, \text{pattern_matching}) \triangleright \text{expr}$	Recursive function helper
$Jfunval$	$::=$	
	$\mid \vdash \text{funval}(e)$	Function values
$JRuprim$	$::=$	
	$\mid \vdash \text{unary_prim expr} \xrightarrow{L} \text{expr}'$	Unary primitive evaluation
$JRbprim$	$::=$	
	$\mid \vdash \text{expr}_1 \text{ binary_prim } \text{expr}_2 \xrightarrow{L} \text{expr}$	Binary primitive evaluation
$JRmatching_step$	$::=$	
	$\mid \vdash \text{expr with pattern_matching} \longrightarrow \text{pattern_matching}'$	Pattern matching step
$JRmatching_success$	$::=$	
	$\mid \vdash \text{expr with pattern_matching} \longrightarrow \text{expr}'$	Pattern matching finished
$Jred$	$::=$	
	$\mid \vdash \text{expr} \xrightarrow{L} \text{expr}'$	

Expression evaluation

$JRdefn$::=	
	$\vdash \langle definitions, program \rangle \xrightarrow{L} \langle definitions', program' \rangle$	Definition sequence evaluation
$JSlookup$::=	
	$store(location) \triangleright expr$	Store lookup
$JRstore$::=	
	$\vdash store \xrightarrow{L} store'$	Store transition
$JRtop$::=	
	$\vdash \langle definitions, program, store \rangle \longrightarrow \langle definitions', program', store' \rangle$	Top-level reduction
$Jebehaviour$::=	
	$\vdash expr \mathbf{behaves}$	Expression behaviour
$Jdbehaviour$::=	
	$\vdash \langle definitions, program, store \rangle \mathbf{behaves}$	structure body behaviour
$judgement$::=	
	$JdomEB$	
	$JdomE$	
	$Jlookup$	
	$Jidx$	
	$JTtps_kind$	
	$JTEok$	

```
| JTeq
| JTidxsub
| JTinst
| JTinst_named
| JTinst_any
| JTval
| JTfield
| JTconstr_p
| JTconstr_c
| JTconst
| JTpat
| JTuprim
| JTbprim
| JTe
| JTconstr_decl
| JTfield_decl
| JTtypedef
| JTtype_definition
| JTdefinition
| JTdefinitions
| JTprog
| JTstore
| JTtop
| JTlin
| JTLout
| JmatchP
| Jmatch
| Jrecfun
| Jfunval
| JRuprim
| JRbprim
| JRmatching_step
| JRmatching_success
```

```

|   Jred
|   JRdefn
|   JSlookup
|   JRstore
|   JRtop
|   Jebehaviour
|   Jdbehaviour

user-syntax ::=

|   index
|   ident
|   integer_literal
|   float_literal
|   char_literal
|   string_literal
|   infix_symbol
|   prefix_symbol
|   location
|   lowercase_ident
|   capitalized_ident
|   value_name
|   operator_name
|   infix_op
|   constr_name
|   typeconstr_name
|   field_name
|   value_path
|   constr
|   typeconstr
|   field
|   idx
|    $\sigma^T$ 
|   typexpr

```

```
| src_typeexpr
|  $\alpha$ 
| typescheme
|  $\dot{n}$ 
| constant
| pattern
| unary-prim
| binary-prim
| expr
| [down]to
| substs_x
| pattern_matching
| pat_exp
| let_binding
| letrec_bindings
| letrec_binding
| type_definition
| typedef
| type_information
| type_equation
| type_representation
| type_params_opt
| type_param
| constr_decl
| field_decl
| exception_definition
| definition
| definitions
| program
| value
| binary-prim-app-value
| definition_value
| definitions_value
```

```
|   non_expansive  
|   store  
|   kind  
|   name  
|   names  
|   typeexprs  
|   environment_binding  
|   environment  
|   trans_label  
|    $\xrightarrow{L}$   
|   formula  
|   terminals
```

A formal specification for OCaml: the Core Language

Scott Owens and Gilles Peskine and Peter Sewell

January 15, 2018

Contents

1	Introduction	4	
2	Syntax	6	
3	Type system	6	
3.1	$\boxed{\text{dom}(EB) \triangleright name}$	Environment binding domain	7
3.2	$\boxed{\text{dom}(E) \triangleright names}$	Environment domain	7
3.3	$E \vdash name \triangleright EB$	Environment lookup	8
3.4	$E \vdash idx \text{ bound}$	Well-formed index	8
3.5	$\vdash type_params_opt : kind$	Type parameter kinding	8
3.6	$E \vdash \text{ok}$	Environment validity	9
3.7	$E \vdash typeconstr : kind$	Type constructor kinding	11
3.8	$E \vdash typescheme : kind$	de Bruijn type scheme well-formedness	12
3.9	$E \vdash \forall type_params_opt, t : kind$	Named type scheme well-formedness	12
3.10	$E \vdash typexpr : kind$	Type expression well-formedness	12
3.11	$E \vdash typexpr \equiv typexpr'$	Type equivalence	13
3.12	$\{\{typexpr_1, \dots, typexpr_n\} typexpr' \triangleright typexpr''$	de Bruin type substitution	14
3.13	$E \vdash typexpr \leq typescheme$	de Bruijn type scheme instantiation	14
3.14	$E \vdash typexpr \leq \forall type_params_opt, typexpr'$	Named type scheme instantiation	15
3.15	$E \vdash typexpr \leq typexpr'$	Wildcard type instantiation	15
3.16	$E \vdash value_name : typexpr$	Variable typing	15
3.17	$E \vdash field_name : typexpr \rightarrow typexpr'$	Field name typing	16
3.18	$E \vdash constr : typexpr_1 \dots typexpr_n \rightarrow typexpr'$	Non-constant constructor typing	16
3.19	$E \vdash constr : typexpr$	Constant constructor typing	16
3.20	$E \vdash constant : typexpr$	Constant typing	17
3.21	$\sigma^T \& E \vdash pattern : typexpr \triangleright E'$	Pattern typing and binding collection	18
3.22	$E \vdash unary_prim : typexpr$	Unary primitive typing	19

3.23	$E \vdash \text{binary_prim} : \text{typexpr}$	Binary primitive typing	20
3.24	$\sigma^T \& E \vdash \text{expr} : \text{typexpr}$	Expression typing	20
3.25	$\sigma^T \& E \vdash \text{pattern_matching} : \text{typexpr} \rightarrow \text{typexpr}'$	Pattern matching/expression pair typing	24
3.26	$\sigma^T \& E \vdash \text{let_binding} \triangleright E'$	Let binding typing	24
3.27	$\sigma^T \& E \vdash \text{letrec_bindings} \triangleright E'$	Recursive let binding typing	25
3.28	$\text{type_params_opt typeconstr} \vdash \text{constr_decl} \triangleright EB$	Variant constructor declaration	25
3.29	$\text{type_params_opt typeconstr_name} \vdash \text{field_decl} \triangleright EB$	Record field declaration	25
3.30	$\vdash \text{typedef}_1 \text{ and.. and } \text{typedef}_n \triangleright E' \text{ and } E'' \text{ and } E'''$	Type definitions collection	25
3.31	$E \vdash \text{type_definition} \triangleright E'$	Type definition well-formedness and binding collection	27
3.32	$E \vdash \text{definition} : E'$	Definition typing	27
3.33	$E \vdash \text{definitions} : E'$	Definition sequence typing	28
3.34	$E \vdash \text{program} : E'$	Program typing	28
3.35	$E \vdash \text{store} : E'$	Store typing	28
3.36	$E \vdash \langle \text{program}, \text{store} \rangle$	Top-level typing	29
3.37	$\sigma^T \& E \vdash L$	Label-to-environment extraction	29
3.38	$\sigma^T \& E \vdash L \triangleright E'$	Label-to-environment extraction	29
4	Operational Semantics		30
4.1	$\vdash \text{expr matches pattern}$	Pattern matching	30
4.2	$\vdash \text{expr matches pattern} \triangleright \{\{ \text{substs}_x \}\}$	Pattern matching with substitution creation	31
4.3	$\text{recfun}(\text{letrec_bindings}, \text{pattern_matching}) \triangleright \text{expr}$	Recursive function helper	32
4.4	$\vdash \text{funval}(e)$	Function values	32
4.5	$\vdash \text{unary_prim expr} \xrightarrow{L} \text{expr}'$	Unary primitive evaluation	33
4.6	$\vdash \text{expr}_1 \text{ binary_prim expr}_2 \xrightarrow{L} \text{expr}$	Binary primitive evaluation	33
4.7	$\vdash \text{expr with pattern_matching} \longrightarrow \text{pattern_matching}'$	Pattern matching step	35
4.8	$\vdash \text{expr with pattern_matching} \longrightarrow \text{expr}'$	Pattern matching finished	35

4.9	$\vdash \text{expr} \xrightarrow{L} \text{expr}'$	Expression evaluation	35
4.10	$\vdash \langle \text{definitions}, \text{program} \rangle \xrightarrow{L} \langle \text{definitions}', \text{program}' \rangle$	Definition sequence evaluation	40
4.11	$\text{store}(\text{location}) \triangleright \text{expr}$	Store lookup	41
4.12	$\vdash \text{store} \xrightarrow{L} \text{store}'$	Store transition	41
4.13	$\vdash \langle \text{definitions}, \text{program}, \text{store} \rangle \longrightarrow \langle \text{definitions}', \text{program}', \text{store}' \rangle$	Top-level reduction	41
4.14	$\vdash \text{expr} \text{ behaves}$	Expression behaviour	42
4.15	$\vdash \langle \text{definitions}, \text{program}, \text{store} \rangle \text{behaves}$	structure body behaviour	42

5	Statistics	42
---	------------	----

1 Introduction

This document describes the syntax and semantics of a substantial fragment of Objective Caml’s core language. When writing this semantics, we have followed the structure of part 2 of the Objective Caml manual:

The Objective Caml system
release 3.09

Documentation and user’s manual
Xavier Leroy (with Damien Doligez, Jacques Garrigue, Didier Rémy and Jérôme Vouillon)
Copyright © 2005 Institut National de Recherche en Informatique et en Automatique

Our aim is to describe a real language, including theoretically redundant but practically useful features. We do not however cover the whole Objective Caml language: we have omitted some major semantic features, such as objects and modules. Our guideline is to retain the semantic features of core ML as implemented in Objective Caml. Our language corresponds roughly to the fragment presented in Chapter 1 of the Objective Caml manual.

Supported features include:

- the following primitive types and type constructors: `int`, `char`, `string`, `float`, `bool`, `unit`, `exn`, `list`, `option`, `ref`;
- tuple and function types
- type and type constructor definitions, including:
 - type abbreviations (e.g., `type t = int`),
 - variant data and record types (e.g., `type t = I of int || D of char` and `type t = {f:int}`),
 - parametric type constructors (e.g., `type 'a t = 'a -> 'a`),

- recursive and mutually recursive combinations of the above (although all recursion must go through a variant data or record type);
- let-based polymorphism (with the traditional ML-style value restriction);
- 31-bit word semantics for integers and IEEE-754 semantics for floating point numbers (in the version of the system generated for HOL);
- type annotations (e.g., `3:int`), list notation (e.g., `[1; 2; 3]`), record `with` expressions, `if` expressions, `while` expressions, `for` expressions, sequencing (`;`), `assert` expressions;
- (potentially) mutually-recursive function definitions;
- pattern matching with nested patterns and `}` patterns;
- mutable references through `ref`, `:=`, and `!;`
- exception definitions and handling (`try`, `raise`, `exception`);
- polymorphic equality (the `=` operator).

The following features are not supported:

- mutable records (e.g., `{mutable l1=e1; ...;mutable ln=en}`);
- arrays;
- modules;
- subtyping, labels, polymorphic variants, objects;
- pattern matching guards (`when`);
- features documented in the “language extensions” part of the manual;
- `-rectypes`, exhaustivity of pattern matching, and other compiler command-line options;
- support for type abbreviations in the HOL model (we explain in the commentary how they should be added);
- finiteness of memory.

This document contains a description of the language syntax (§2), a type system (§3) and an operational semantics (§4).

Metatheory This typeset definition is generated by `ott`. Well-formed definitions in HOL, Isabelle/HOL and Coq are also generated. We have mechanized the type soundness theorem for the system in HOL.

2 Syntax

We describe the syntax of the core OCaml language in BNF form, closely following the description in the Objective Caml manual, but omitting unsupported language features. The concrete syntax of Objective Caml includes lexical specifications as well as precedence rules to disambiguate the grammar; we do not reproduce these here.

Some productions mention annotations to the right of the right-hand side. The following annotations are understood by Ott.

- M indicates a metaproduction. These are not part of the free grammar for the relevant nonterminal. Instead they are given meaning (in the theorem prover models) by translation into non-metaproductions. These translations, specified in the Ott source, are specific to each theorem prover. We summarize their action in this document.
- S indicates a metaproduction that is implemented as syntactic sugar.
- “bind ...” and “auxfun = ...” are Ott binding specifications.

The following annotations are for informational purposes only.

- [I] indicates a production that is not intended to be available in user programs but is useful in the metatheory.
- [L] indicates a library facility (as opposed to a strictly language facility).
- d indicates a definition-level feature, if enabled.

3 Type system

The Objective Caml manual does not describe the type system. Therefore our semantics is driven by an attempt to mirror what the Objective Caml implementation does, drawing inspiration from various presentations of type systems for ML. Some notable aspects of the formalization follow:

- We give a declarative presentation of polymorphic typing, i.e., without unification.
- Polymorphic **let** introduces type variables which are encoded with de Bruijn indices.
- Several rules have premises that state there are at least 1 (or 2) elements of a list, despite there being 3 or 4 dots. This is because Ott does not use dot imposed length restrictions in the theorem prover models.
- Occasionally, we state that some list $X_1 \dots X_m$ has length m. Ott does not impose this restriction in the theorem prover models either.

3.1 $\boxed{\text{dom}(EB) \triangleright name}$ Environment binding domain

Gets the name of an environment entry.

$$\begin{array}{c}
 \frac{}{\text{dom}(\text{TV}) \triangleright \text{TV}} \quad \text{JdomEB_type_param} \\
 \frac{\text{dom}(value_name : typescheme) \triangleright value_name}{\text{dom}(constr_name \text{ of } typeconstr) \triangleright constr_name} \quad \text{JdomEB_value_name} \\
 \frac{\text{dom}(constr_name \text{ of } typeconstr) \triangleright constr_name}{\text{dom}(constr_name \text{ of } \forall type_params_opt, (t_1, \dots, t_n) : typeconstr) \triangleright constr_name} \quad \text{JdomEB_const_constr_name} \\
 \frac{\text{dom}(typeconstr_name : kind) \triangleright typeconstr_name}{\text{dom}(type_params_opt typeconstr_name = t) \triangleright typeconstr_name} \quad \text{JdomEB_opaque_typeconstr_name} \\
 \frac{\text{dom}(typeconstr_name : kind\{field_name_1; \dots; field_name_n\}) \triangleright typeconstr_name}{\text{dom}(field_name : \forall type_params_opt, typeconstr_name \rightarrow typexpr) \triangleright field_name} \quad \text{JdomEB_record_typeconstr_name} \\
 \frac{\text{dom}(location : t) \triangleright location}{\text{dom}(E) \triangleright names} \quad \text{JdomEB_location}
 \end{array}$$

3.2 $\boxed{\text{dom}(E) \triangleright names}$ Environment domain

Gets all of the names in an environment.

$$\frac{}{\text{dom}(\text{empty}) \triangleright} \quad \text{JdomE_empty} \\
 \frac{\text{dom}(E) \triangleright name_1 .. name_n \quad \text{dom}(EB) \triangleright name}{\text{dom}(E, EB) \triangleright name name_1 .. name_n} \quad \text{JdomE_cons}$$

3.3 $E \vdash name \triangleright EB$ Environment lookup

Returns the rightmost binding that matches the given name.

$$\begin{array}{c}
 \frac{\text{dom}(EB) \triangleright name' \\
 name \neq name' \\
 name' \neq \mathbf{TV} \\
 E \vdash name \triangleright EB'}{E, EB \vdash name \triangleright EB'} \quad \text{Jlookup_EB_rec1} \\
 \\
 \frac{\text{name} \neq \mathbf{TV} \\
 E \vdash name \triangleright EB'}{E, \mathbf{TV} \vdash name \triangleright \text{shift } 0\ 1\ EB'} \quad \text{Jlookup_EB_rec2} \\
 \\
 \frac{\text{dom}(EB) \triangleright name}{E, EB \vdash name \triangleright EB} \quad \text{Jlookup_EB_head}
 \end{array}$$

3.4 $E \vdash idx \text{ bound}$ Well-formed index

Determines whether an index is bound by an environment.

$$\begin{array}{c}
 \frac{E \vdash idx \text{ bound} \\
 \text{dom}(EB) \triangleright name \\
 name \neq \mathbf{TV}}{E, EB \vdash idx \text{ bound}} \quad \text{Jidx_bound_skip1} \\
 \\
 \frac{E \vdash idx \text{ bound}}{E, \mathbf{TV} \vdash idx + 1 \text{ bound}} \quad \text{Jidx_bound_skip2} \\
 \\
 \frac{}{E, \mathbf{TV} \vdash 0 \text{ bound}} \quad \text{Jidx_bound_found}
 \end{array}$$

3.5 $\vdash type_params_opt : kind$ Type parameter kinding

Counts the number of parameters and ensures that none is repeated.

$$\frac{tp_1 \dots tp_n \text{ distinct} \\
 \text{length}(tp_1) \dots (tp_n) = n}{\vdash (tp_1, \dots, tp_n) : \mathbf{Type}^n \rightarrow \mathbf{Type}} \quad \text{JTtps_kind_kind}$$

3.6 $E \vdash \text{ok}$ Environment validity

Asserts that the various components of the environment are well-formed (including that there are no free type references), and regulates name shadowing. Environments contain identifiers related to type definitions and type variables as well as expression-level variables (i.e., value names), so they are dependent from left to right. Shadowing of type, constructor, field and label names is forbidden, but shadowing of value names is allowed.

$$\begin{array}{c}
\frac{}{\mathbf{empty} \vdash \mathbf{ok}} \quad \text{JTEok_empty} \\
\\
\frac{E \vdash \mathbf{ok}}{E, \mathbf{TV} \vdash \mathbf{ok}} \quad \text{JTEok_typevar} \\
\\
\frac{E \vdash \forall t : \mathbf{Type}}{E, (\text{value_name} : \forall t) \vdash \mathbf{ok}} \quad \text{JTEok_value_name} \\
\\
\frac{\begin{array}{l} E \vdash \mathbf{ok} \\ E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \mathbf{kind} \\ \mathbf{dom}(E) \triangleright \mathbf{names} \\ \mathbf{constr_name} \notin \mathbf{names} \end{array}}{E, (\mathbf{constr_name} \mathbf{of} \text{typeconstr_name}) \vdash \mathbf{ok}} \quad \text{JTEok_constr_name_c} \\
\\
\frac{\begin{array}{l} E \vdash \mathbf{ok} \\ \mathbf{dom}(E) \triangleright \mathbf{names} \\ \mathbf{constr_name} \notin \mathbf{names} \end{array}}{E, (\mathbf{constr_name} \mathbf{of} \mathbf{exn}) \vdash \mathbf{ok}} \quad \text{JTEok_exn_constr_name_c} \\
\\
\frac{\begin{array}{l} \mathbf{type_params_opt} = (\alpha_1, \dots, \alpha_m) \\ E \vdash \forall \mathbf{type_params_opt}, t_1 : \mathbf{Type} \dots E \vdash \forall \mathbf{type_params_opt}, t_n : \mathbf{Type} \\ E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \mathbf{Type}^m \rightarrow \mathbf{Type} \\ \mathbf{dom}(E) \triangleright \mathbf{names} \\ \mathbf{constr_name} \notin \mathbf{names} \\ \mathbf{length}(t_1) \dots (t_n) \geq 1 \\ \mathbf{length}(\alpha_1) \dots (\alpha_m) = m \end{array}}{E, (\mathbf{constr_name} \mathbf{of} \forall (\alpha_1, \dots, \alpha_m), (t_1, \dots, t_n) : \text{typeconstr_name}) \vdash \mathbf{ok}} \quad \text{JTEok_constr_name_p}
\end{array}$$

$$\begin{array}{c}
\frac{\begin{array}{c} E \vdash t_1 : \mathbf{Type} \dots E \vdash t_n : \mathbf{Type} \\ \mathbf{dom}(E) \triangleright names \\ constr_name \notin names \\ \mathbf{length}(t_1) \dots (t_n) \geq 1 \end{array}}{E, (constr_name \text{ of } \forall, (t_1, \dots, t_n) : \mathbf{exn}) \vdash \mathbf{ok}} \quad \text{JTEok_exn_constr_name_p} \\
\\
\frac{\begin{array}{c} E \vdash \forall(\alpha_1, \dots, \alpha_m), t : \mathbf{Type} \\ \mathbf{dom}(E) \triangleright names \\ field_name \notin names \\ E \vdash typeconstr_name \triangleright typeconstr_name : \mathbf{Type}^m \rightarrow \mathbf{Type}\{field_name_1; \dots; field_name_n\} \\ \mathbf{length}(\alpha_1) \dots (\alpha_m) = m \\ field_name \text{ in } field_name_1 \dots field_name_n \end{array}}{E, (field_name : \forall(\alpha_1, \dots, \alpha_m), typeconstr_name \rightarrow t) \vdash \mathbf{ok}} \quad \text{JTEok_record_destr} \\
\\
\frac{\begin{array}{c} E \vdash \mathbf{ok} \\ \mathbf{dom}(E) \triangleright names \\ typeconstr_name \notin names \end{array}}{E, (typeconstr_name : kind) \vdash \mathbf{ok}} \quad \text{JTEok_typeconstr_name} \\
\\
\frac{\begin{array}{c} \mathbf{dom}(E) \triangleright names \\ typeconstr_name \notin names \\ E \vdash \forall(\alpha_1, \dots, \alpha_m), t : \mathbf{Type} \end{array}}{E, ((\alpha_1, \dots, \alpha_m) typeconstr_name = t) \vdash \mathbf{ok}} \quad \text{JTEok_typeconstr_eqn} \\
\\
\frac{\begin{array}{c} E \vdash \mathbf{ok} \\ \mathbf{dom}(E) \triangleright names \\ typeconstr_name \notin names \\ field_name_1 \dots field_name_n \text{ distinct} \end{array}}{E, (typeconstr_name : kind\{field_name_1; \dots; field_name_n\}) \vdash \mathbf{ok}} \quad \text{JTEok_typeconstr_record} \\
\\
\frac{\begin{array}{c} E \vdash t : \mathbf{Type} \\ \mathbf{dom}(E) \triangleright names \\ location \notin names \end{array}}{E, (location : t) \vdash \mathbf{ok}} \quad \text{JTEok_location}
\end{array}$$

3.7 $E \vdash \text{typeconstr} : \text{kind}$

Type constructor kinding

Ensures that the type constructor is either defined in the environment or built-in. The result kind indicates how many parameters the type constructor expects.

$$\begin{array}{c}
 \frac{\begin{array}{c} E \vdash \text{ok} \\ E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \text{kind} \end{array}}{E \vdash \text{typeconstr_name} : \text{kind}} \quad \text{JTtypeconstr_abstract} \\
 \\
 \frac{\begin{array}{c} E \vdash \text{ok} \\ E \vdash \text{typeconstr_name} \triangleright \text{type_params_opt} \text{ typeconstr_name} = t \\ \vdash \text{type_params_opt} : \text{kind} \end{array}}{E \vdash \text{typeconstr_name} : \text{kind}} \quad \text{JTtypeconstr_concrete} \\
 \\
 \frac{\begin{array}{c} E \vdash \text{ok} \\ E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \text{kind}\{\text{field_name}_1; \dots; \text{field_name}_n\} \\ E \vdash \text{typeconstr_name} : \text{kind} \end{array}}{E \vdash \text{typeconstr_name} : \text{kind}} \quad \text{JTtypeconstr_record} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{int} : \text{Type}} \quad \text{JTtypeconstr_int} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{char} : \text{Type}} \quad \text{JTtypeconstr_char} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{string} : \text{Type}} \quad \text{JTtypeconstr_string} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{float} : \text{Type}} \quad \text{JTtypeconstr_float} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{bool} : \text{Type}} \quad \text{JTtypeconstr_bool} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{unit} : \text{Type}} \quad \text{JTtypeconstr_unit} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{exn} : \text{Type}} \quad \text{JTtypeconstr_exn} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{list} : \text{Type}^1 \rightarrow \text{Type}} \quad \text{JTtypeconstr_list} \\
 \\
 \frac{E \vdash \text{ok}}{E \vdash \text{option} : \text{Type}^1 \rightarrow \text{Type}} \quad \text{JTtypeconstr_option}
 \end{array}$$

$$\frac{E \vdash \text{ok}}{E \vdash \text{ref} : \text{Type}^1 \rightarrow \text{Type}} \quad \text{JTtypeconstr_ref}$$

3.8 $E \vdash \text{typescheme} : \text{kind}$ de Bruijn type scheme well-formedness

Ensures that the type is well-formed in an extended environment.

$$\frac{E, \mathbf{TV} \vdash t : \text{Type}}{E \vdash \forall t : \text{Type}} \quad \text{JTts_forall}$$

3.9 $E \vdash \forall \text{type_params_opt}, t : \text{kind}$ Named type scheme well-formedness

Ensures that the named type parameters are distinct, and that the type is well-formed. Instead of extending the environment, this simply substitutes a collection of well-formed types, here **unit**. This works because the type well-formedness judgment below only depends on well-formedness of sub-expressions, and not on the exact form of sub-expressions.

$$\frac{\begin{array}{c} E \vdash \{\alpha_1 \leftarrow \text{unit}, \dots, \alpha_n \leftarrow \text{unit}\} t : \text{Type} \\ \alpha_1 \dots \alpha_n \text{ distinct} \end{array}}{E \vdash \forall (\alpha_1, \dots, \alpha_n), t : \text{Type}} \quad \text{JTtsnamed_forall}$$

3.10 $E \vdash \text{typexpr} : \text{kind}$ Type expression well-formedness

Ensures that all of the indices and constructors that appear in a type are bound in the environment.

$$\frac{\begin{array}{c} E \vdash \text{ok} \\ E \vdash \text{idx bound} \end{array}}{E \vdash \langle \text{idx}, \text{num} \rangle : \text{Type}} \quad \text{JTt_var}$$

$$\frac{E \vdash t : \text{Type} \quad E \vdash t' : \text{Type}}{E \vdash t \rightarrow t' : \text{Type}} \quad \text{JTt_arrow}$$

$$\frac{E \vdash t_1 : \text{Type} \quad \dots \quad E \vdash t_n : \text{Type} \quad \text{length}(t_1) \dots (t_n) \geq 2}{E \vdash t_1 * \dots * t_n : \text{Type}} \quad \text{JTt_tuple}$$

$$\frac{\begin{array}{c} E \vdash typeconstr : \mathbf{Type}^n \rightarrow \mathbf{Type} \\ E \vdash t_1 : \mathbf{Type} \quad \dots \quad E \vdash t_n : \mathbf{Type} \\ \mathbf{length}(t_1) \dots (t_n) = n \end{array}}{E \vdash (t_1, \dots, t_n) typeconstr : \mathbf{Type}} \text{ JTt_constr}$$

3.11 $E \vdash typexpr \equiv typexpr'$ Type equivalence

Checks whether two types are related (potentially indirectly) by the type abbreviations in the environment. The system does not allow recursive types that do not pass through an opaque (generative) type constructor, i.e., a variant or record. Therefore all type expressions have a canonical form obtained by expanding all type abbreviations.

$$\frac{\begin{array}{c} E \vdash t : \mathbf{Type} \\ E \vdash t \equiv t \end{array}}{E \vdash t \equiv t} \text{ JTeq_refl}$$

$$\frac{E \vdash t' \equiv t}{E \vdash t \equiv t'} \text{ JTeq_sym}$$

$$\frac{\begin{array}{c} E \vdash t \equiv t' \\ E \vdash t' \equiv t'' \end{array}}{E \vdash t \equiv t''} \text{ JTeq_trans}$$

$$\frac{\begin{array}{c} E \vdash \mathbf{ok} \\ E \vdash typeconstr_name \triangleright (\alpha_1, \dots, \alpha_n) typeconstr_name = t \\ E \vdash t_1 : \mathbf{Type} \quad \dots \quad E \vdash t_n : \mathbf{Type} \end{array}}{E \vdash (t_1, \dots, t_n) typeconstr_name \equiv \{\alpha_1 \leftarrow t_1, \dots, \alpha_n \leftarrow t_n\} t} \text{ JTeq_expand}$$

$$\frac{\begin{array}{c} E \vdash t_1 \equiv t'_1 \\ E \vdash t_2 \equiv t'_2 \end{array}}{E \vdash t_1 \rightarrow t_2 \equiv t'_1 \rightarrow t'_2} \text{ JTeq_arrow}$$

$$\frac{\begin{array}{c} E \vdash t_1 \equiv t'_1 \quad \dots \quad E \vdash t_n \equiv t'_n \\ \mathbf{length}(t_1) \dots (t_n) \geq 2 \end{array}}{E \vdash t_1 * \dots * t_n \equiv t'_1 * \dots * t'_n} \text{ JTeq_tuple}$$

$$\frac{\begin{array}{c} E \vdash typeconstr : \mathbf{Type}^n \rightarrow \mathbf{Type} \\ E \vdash t_1 \equiv t'_1 \quad \dots \quad E \vdash t_n \equiv t'_n \\ \mathbf{length}(t_1) \dots (t_n) = n \end{array}}{E \vdash (t_1, \dots, t_n) typeconstr \equiv (t'_1, \dots, t'_n) typeconstr} \text{ JTeq_constr}$$

3.12 $\boxed{\{typexpr_1, \dots, typexpr_n\}typexpr' \triangleright typexpr''}$ de Bruin type substitution

Replaces index 0 position n with the n th type in the list, and reduces all other indices by 1.

$$\begin{array}{c}
 \frac{}{\{t_1, \dots, t_n\}\alpha \triangleright \alpha} \text{ JTinxsub_alpha} \\
 \\
 \frac{\text{length}(t_1) .. (t_m) = num}{\{t_1, \dots, t_m, t', t''_1, \dots, t''_n\} < 0, num > \triangleright t'} \text{ JTinxsub_idx0} \\
 \\
 \frac{\text{length}(t_1) .. (t_n) \leq num}{\{t_1, \dots, t_n\} < 0, num > \triangleright \text{unit}} \text{ JTinxsub_idx1} \\
 \\
 \frac{}{\{t_1, \dots, t_n\} < idx + 1, num > \triangleright \langle idx, num \rangle} \text{ JTinxsub_idx2} \\
 \\
 \frac{}{\{t_1, \dots, t_n\}_- \triangleright -} \text{ JTinxsub_any} \\
 \\
 \frac{\begin{array}{c} \{t_1, \dots, t_n\} t'_1 \triangleright t''_1 \\ \{t_1, \dots, t_n\} t'_2 \triangleright t''_2 \end{array}}{\{t_1, \dots, t_n\} (t'_1 \rightarrow t'_2) \triangleright t''_1 \rightarrow t''_2} \text{ JTinxsub_arrow} \\
 \\
 \frac{\{t_1, \dots, t_n\} t'_1 \triangleright t''_1 \dots \{t_1, \dots, t_n\} t'_m \triangleright t''_m}{\{t_1, \dots, t_n\} (t'_1 * \dots * t'_m) \triangleright (t''_1 * \dots * t''_m)} \text{ JTinxsub_tuple} \\
 \\
 \frac{\{t_1, \dots, t_n\} t'_1 \triangleright t''_1 \dots \{t_1, \dots, t_n\} t'_m \triangleright t''_m}{\{t_1, \dots, t_n\} (t'_1, \dots, t'_m) \text{typeconstr} \triangleright (t''_1, \dots, t''_m) \text{typeconstr}} \text{ JTinxsub_tc}
 \end{array}$$

3.13 $\boxed{E \vdash typexpr \leq typescheme}$ de Bruijn type scheme instantiation

Replaces all of the bound variables of a type scheme.

$$\frac{\begin{array}{c} E \vdash \forall t' : \text{Type} \\ E \vdash t_1 : \text{Type} \dots E \vdash t_n : \text{Type} \\ \{t_1, \dots, t_n\} t' \triangleright t'' \end{array}}{E \vdash t'' \leq \forall t'} \text{ JTinst_idx}$$

3.14 $E \vdash \text{typexpr} \leq \forall \text{type_params_opt}, \text{typexpr}'$ **Named type scheme instantiation**

Replaces all of the bound variables of a named type scheme.

$$\frac{\begin{array}{c} E \vdash \forall (\alpha_1, \dots, \alpha_n), t : \mathbf{Type} \\ E \vdash t_1 : \mathbf{Type} \quad \dots \quad E \vdash t_n : \mathbf{Type} \end{array}}{E \vdash \{\alpha_1 \leftarrow t_1, \dots, \alpha_n \leftarrow t_n\} t \leq \forall (\alpha_1, \dots, \alpha_n), t} \text{ JTinst_named_named}$$

3.15 $E \vdash \text{typexpr} \leq \text{typexpr}'$ **Wildcard type instantiation**

Replaces $_$ type variables with arbitrary types.

$$\frac{E \vdash \langle idx, num \rangle : \mathbf{Type}}{E \vdash \langle idx, num \rangle \leq \langle idx, num \rangle} \text{ JTinst_any_tyvar}$$

$$\frac{E \vdash t : \mathbf{Type}}{E \vdash t \leq _} \text{ JTinst_any_any}$$

$$\frac{\begin{array}{c} E \vdash t_1 \leq t'_1 \\ E \vdash t_2 \leq t'_2 \end{array}}{E \vdash t_1 \rightarrow t_2 \leq t'_1 \rightarrow t'_2} \text{ JTinst_any_arrow}$$

$$\frac{\begin{array}{c} E \vdash t_1 \leq t'_1 \quad \dots \quad E \vdash t_n \leq t'_n \\ \mathbf{length}(t_1) \dots (t_n) \geq 2 \end{array}}{E \vdash t_1 * \dots * t_n \leq t'_1 * \dots * t'_n} \text{ JTinst_any_tuple}$$

$$\frac{\begin{array}{c} E \vdash t_1 \leq t'_1 \quad \dots \quad E \vdash t_n \leq t'_n \\ E \vdash \text{typeconstr} : \mathbf{Type}^n \rightarrow \mathbf{Type} \\ \mathbf{length}(t_1) \dots (t_n) = n \end{array}}{E \vdash (t_1, \dots, t_n) \text{typeconstr} \leq (t'_1, \dots, t'_n) \text{typeconstr}} \text{ JTinst_any_ctor}$$

3.16 $E \vdash \text{value_name} : \text{typexpr}$ **Variable typing**

Determines if a variable can have a specified type.

$$\frac{\begin{array}{c} E \vdash \text{value_name} \triangleright \text{value_name} : ts \\ E \vdash t \leq ts \end{array}}{E \vdash \text{value_name} : t} \text{ JTvalue_name_value_name}$$

3.17 $E \vdash \text{field_name} : \text{typexpr} \rightarrow \text{typexpr}'$

Field name typing

Determines the type constructor associated with a given field name. Since field names are used to destructure record data, the type is a function type from a record to the type of the corresponding position.

$$\frac{\begin{array}{c} E \vdash \text{field_name} \triangleright \text{field_name} : \forall(\alpha_1, \dots, \alpha_m), \text{typeconstr_name} \rightarrow t \\ E \vdash (t'_1, \dots, t'_m) \text{typeconstr_name} \rightarrow t'' \leq \forall(\alpha_1, \dots, \alpha_m), (\alpha_1, \dots, \alpha_m) \text{typeconstr_name} \rightarrow t \end{array}}{E \vdash \text{field_name} : (t'_1, \dots, t'_m) \text{typeconstr_name} \rightarrow t''} \text{JTfield_name}$$

3.18 $E \vdash \text{constr} : \text{typexpr}_1 \dots \text{typexpr}_n \rightarrow \text{typexpr}'$

Non-constant constructor typing

Determines the type constructor associated with a given value constructor. Non-constant constructors are attributed types for each argument as well as a return type.

$$\frac{\begin{array}{c} E \vdash \text{constr_name} \triangleright \text{constr_name of } \forall(\alpha_1, \dots, \alpha_m), (t_1, \dots, t_n) : \text{typeconstr} \\ E \vdash (t'_1 * \dots * t'_n) \rightarrow (t''_1, \dots, t''_m) \text{typeconstr} \leq \forall(\alpha_1, \dots, \alpha_m), (t_1 * \dots * t_n) \rightarrow (\alpha_1, \dots, \alpha_m) \text{typeconstr} \end{array}}{E \vdash \text{constr_name} : t'_1 \dots t'_n \rightarrow (t''_1, \dots, t''_m) \text{typeconstr}} \text{JTconstr_p_name}$$

$$\frac{E \vdash \text{ok}}{E \vdash \text{Invalid_argument} : \text{string} \rightarrow \text{exn}} \text{JTconstr_p_invarg}$$

$$\frac{E \vdash t : \text{Type}}{E \vdash \text{Some} : t \rightarrow (t \text{ option})} \text{JTconstr_p_some}$$

3.19 $E \vdash \text{constr} : \text{typexpr}$

Constant constructor typing

Constant constructors are typed like non-constant constructors without arguments.

$$\frac{\begin{array}{c} E \vdash \text{ok} \\ E \vdash \text{constr_name} \triangleright \text{constr_name of } \text{typeconstr_name} \\ E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \text{Type}^n \rightarrow \text{Type} \\ E \vdash t_1 : \text{Type} \dots E \vdash t_n : \text{Type} \\ \text{length}(t_1) \dots (t_n) = n \end{array}}{E \vdash \text{constr_name} : (t_1, \dots, t_n) \text{typeconstr_name}} \text{JTconstr_c_constr}$$

$$\begin{array}{c}
 \frac{E \vdash \text{ok}}{E \vdash \text{constr_name} \triangleright \text{constr_name of exn}} \quad \text{JTconstr_c_exn_constr} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{constr_name} : \text{exn}} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{Not_found} : \text{exn}} \quad \text{JTconstr_c_notfound} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{Assert_failure} : \text{exn}} \quad \text{JTconstr_c_assert_fail} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{Match_failure} : \text{exn}} \quad \text{JTconstr_c_match_fail}
 \end{array}$$

Dropping the source location arguments for **Assert_failure** and **Match_failure**.

$$\begin{array}{c}
 \frac{E \vdash \text{ok}}{E \vdash \text{Division_by_zero} : \text{exn}} \quad \text{JTconstr_c_div_by_0} \\
 \frac{E \vdash t : \text{Type}}{E \vdash \text{None} : t \text{ option}} \quad \text{JTconstr_c_none}
 \end{array}$$

3.20 $E \vdash \text{constant} : \text{typexpr}$ Constant typing

Determines the type of a constant.

$$\begin{array}{c}
 \frac{E \vdash \text{ok}}{E \vdash \text{integer_literal} : \text{int}} \quad \text{JTconst_int} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{float_literal} : \text{float}} \quad \text{JTconst_float} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{char_literal} : \text{char}} \quad \text{JTconst_char} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{string_literal} : \text{string}} \quad \text{JTconst_string} \\
 \frac{E \vdash \text{constr} : t}{E \vdash \text{constr} : t} \quad \text{JTconst_constr} \\
 \frac{E \vdash \text{ok}}{E \vdash \text{false} : \text{bool}} \quad \text{JTconst_false}
 \end{array}$$

$$\begin{array}{c}
 \frac{E \vdash \text{ok}}{E \vdash \text{true} : \text{bool}} \quad \text{JTconst_true} \\
 \frac{E \vdash \text{ok}}{E \vdash () : \text{unit}} \quad \text{JTconst_unit} \\
 \frac{E \vdash t : \text{Type}}{E \vdash [] : t \text{ list}} \quad \text{JTconst_nil}
 \end{array}$$

3.21 $\sigma^T \& E \vdash \text{pattern} : \text{typexpr} \triangleright E'$ **Pattern typing and binding collection**

Determines if a pattern matches a value of a certain type, and calculates the types of the variables it binds. A pattern must bind any given variable at most once, except that the two alternatives of an or-pattern must bind the same set of variables. σ^T gives the types that should replace type variables in explicitly type-annotated patterns.

$$\begin{array}{c}
 \frac{E \vdash t : \text{Type}}{\sigma^T \& E \vdash x : t \triangleright x : t} \quad \text{JTpat_var} \\
 \frac{E \vdash t : \text{Type}}{\sigma^T \& E \vdash _ : t \triangleright \text{empty}} \quad \text{JTpat_any} \\
 \frac{E \vdash \text{constant} : t}{\sigma^T \& E \vdash \text{constant} : t \triangleright \text{empty}} \quad \text{JTpat_constant} \\
 \frac{\sigma^T \& E \vdash \text{pattern} : t \triangleright E' \\
 \text{dom}(E', x : t) \triangleright \text{name}_1 .. \text{name}_n \\
 \text{name}_1 .. \text{name}_n \text{ distinct}}{\sigma^T \& E \vdash \text{pattern as } x : t \triangleright E', x : t} \quad \text{JTpat_alias} \\
 \frac{\sigma^T \& E \vdash \text{pattern} : t \triangleright E' \\
 E \vdash t' \leq \sigma^T \text{src_}t \\
 E \vdash t \equiv t'}{\sigma^T \& E \vdash (\text{pattern} : \text{src_}t) : t \triangleright E'} \quad \text{JTpat_typed} \\
 \frac{\sigma^T \& E \vdash \text{pattern} : t \triangleright E' \\
 \sigma^T \& E \vdash \text{pattern}' : t \triangleright E'' \\
 E' \text{ PERMUTES } E''}{\sigma^T \& E \vdash \text{pattern} | \text{pattern}' : t \triangleright E'} \quad \text{JTpat_or}
 \end{array}$$

$$\begin{array}{c}
E \vdash constr : t_1 \dots t_n \rightarrow t \\
\sigma^T \& E \vdash pattern_1 : t_1 \triangleright E_1 \dots \sigma^T \& E \vdash pattern_n : t_n \triangleright E_n \\
\text{dom}(E_1 @ \dots @ E_n) \triangleright name_1 .. name_m \\
name_1 .. name_m \text{ distinct} \\
\hline
\sigma^T \& E \vdash constr(pattern_1, \dots, pattern_n) : t \triangleright E_1 @ \dots @ E_n \quad \text{JTpat_construct}
\end{array}$$

$$\frac{E \vdash constr : t_1 \dots t_n \rightarrow t}{\sigma^T \& E \vdash constr_ : t \triangleright \text{empty}} \quad \text{JTpat_construct_any}$$

$$\begin{array}{c}
\sigma^T \& E \vdash pattern_1 : t_1 \triangleright E_1 \dots \sigma^T \& E \vdash pattern_n : t_n \triangleright E_n \\
\text{length}(pattern_1) \dots (pattern_n) \geq 2 \\
\text{dom}(E_1 @ \dots @ E_n) \triangleright name_1 .. name_m \\
name_1 .. name_m \text{ distinct} \\
\hline
\sigma^T \& E \vdash pattern_1, \dots, pattern_n : t_1 * \dots * t_n \triangleright E_1 @ \dots @ E_n \quad \text{JTpat_tuple}
\end{array}$$

$$\begin{array}{c}
\sigma^T \& E \vdash pattern_1 : t_1 \triangleright E_1 \dots \sigma^T \& E \vdash pattern_n : t_n \triangleright E_n \\
E \vdash field_name_1 : t \rightarrow t_1 \dots E \vdash field_name_n : t \rightarrow t_n \\
\text{length}(pattern_1) \dots (pattern_n) \geq 1 \\
\text{dom}(E_1 @ \dots @ E_n) \triangleright name_1 .. name_m \\
name_1 .. name_m \text{ distinct} \\
\hline
\sigma^T \& E \vdash \{field_name_1 = pattern_1; \dots; field_name_n = pattern_n\} : t \triangleright E_1 @ \dots @ E_n \quad \text{JTpat_record}
\end{array}$$

$$\begin{array}{c}
\sigma^T \& E \vdash pattern : t \triangleright E' \\
\sigma^T \& E \vdash pattern' : t \text{ list} \triangleright E'' \\
\text{dom}(E') \triangleright name_1 .. name_m \\
\text{dom}(E'') \triangleright name'_1 .. name'_n \\
name_1 .. name_m name'_1 .. name'_n \text{ distinct} \\
\hline
\sigma^T \& E \vdash pattern :: pattern' : t \text{ list} \triangleright E' @ E'' \quad \text{JTpat_cons}
\end{array}$$

3.22 $\boxed{E \vdash \text{unary_prim} : \text{typexpr}}$ Unary primitive typing

Determines if a unary primitive has a given type.

$$\frac{E \vdash t : \text{Type}}{E \vdash \text{raise} : \text{exn} \rightarrow t} \quad \text{JTuprim_raise}$$

$$\frac{E \vdash \text{ok}}{E \vdash \text{not} : \text{bool} \rightarrow \text{bool}} \quad \text{JTuprim_not}$$

$$\begin{array}{c}
 \frac{E \vdash \text{ok}}{E \vdash \sim : \text{int} \rightarrow \text{int}} \quad \text{JTuprim_uminus} \\
 \frac{E \vdash t : \text{Type}}{E \vdash \text{ref} : t \rightarrow (\text{t ref})} \quad \text{JTuprim_ref} \\
 \frac{E \vdash t : \text{Type}}{E \vdash ! : (\text{t ref}) \rightarrow t} \quad \text{JTuprim_deref}
 \end{array}$$

3.23 $E \vdash \text{binary_prim} : \text{typexpr}$ Binary primitive typing

Determines if a binary primitive has a given type.

$$\begin{array}{c}
 \frac{E \vdash t : \text{Type}}{E \vdash = : t \rightarrow (t \rightarrow \text{bool})} \quad \text{JTbprim_equal} \\
 \frac{E \vdash \text{ok}}{E \vdash + : \text{int} \rightarrow (\text{int} \rightarrow \text{int})} \quad \text{JTbprim_plus} \\
 \frac{E \vdash \text{ok}}{E \vdash - : \text{int} \rightarrow (\text{int} \rightarrow \text{int})} \quad \text{JTbprim_minus} \\
 \frac{E \vdash \text{ok}}{E \vdash * : \text{int} \rightarrow (\text{int} \rightarrow \text{int})} \quad \text{JTbprim_times} \\
 \frac{E \vdash \text{ok}}{E \vdash / : \text{int} \rightarrow (\text{int} \rightarrow \text{int})} \quad \text{JTbprim_div} \\
 \frac{E \vdash t : \text{Type}}{E \vdash := \text{t ref} \rightarrow (t \rightarrow \text{unit})} \quad \text{JTbprim_assign}
 \end{array}$$

3.24 $\sigma^T \& E \vdash \text{expr} : \text{typexpr}$ Expression typing

Determines if an expression has a given type. Note that t is a type, not a type scheme, but it may contain type variables (which are recorded in E). σ^T gives the types that should replace type variables in explicitly type-annotated patterns.

While the choice of a rule is mostly syntax-directed (for any given constructor, a single rule applies, except for **let** and **assert**), polymorphism is handled in a purely declarative manner. The choice of instantiation for a polymorphic bound variable or primitive is free, as is the number of variables introduced by a polymorphic **let**.

$$\begin{array}{c}
 \frac{E \vdash \text{unary_prim} : t \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash (\% \mathbf{prim} \text{unary_prim}) : t'} \quad \text{JTe_uprim} \\
 \frac{E \vdash \text{binary_prim} : t \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash (\% \mathbf{prim} \text{binary_prim}) : t'} \quad \text{JTe_bprim} \\
 \frac{E \vdash \text{value_name} : t \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash \text{value_name} : t'} \quad \text{JTe_ident} \\
 \frac{E \vdash \text{constant} : t \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash \text{constant} : t'} \quad \text{JTe_constant} \\
 \frac{\sigma^T \& E \vdash e : t \quad E \vdash t' \leq \sigma^T \text{src_t} \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash (e : \text{src_t}) : t} \quad \text{JTe_typed} \\
 \frac{\sigma^T \& E \vdash e_1 : t_1 \dots \sigma^T \& E \vdash e_n : t_n \quad \text{length}(e_1) \dots (e_n) \geq 2 \quad E \vdash t_1 * \dots * t_n \equiv t'}{\sigma^T \& E \vdash e_1, \dots, e_n : t'} \quad \text{JTe_tuple} \\
 \frac{E \vdash \text{constr} : t_1 \dots t_n \rightarrow t \quad \sigma^T \& E \vdash e_1 : t_1 \dots \sigma^T \& E \vdash e_n : t_n \quad E \vdash t \equiv t'}{\sigma^T \& E \vdash \text{constr}(e_1, \dots, e_n) : t'} \quad \text{JTe_construct} \\
 \frac{\sigma^T \& E \vdash e_1 : t \quad \sigma^T \& E \vdash e_2 : t \text{ list} \quad E \vdash t \text{ list} \equiv t'}{\sigma^T \& E \vdash e_1 :: e_2 : t'} \quad \text{JTe_cons}
 \end{array}$$

$$\begin{array}{c}
\sigma^T \& E \vdash e_1 : t_1 \dots \sigma^T \& E \vdash e_n : t_n \\
E \vdash \text{field_name}_1 : t \rightarrow t_1 \dots E \vdash \text{field_name}_n : t \rightarrow t_n \\
t = (t'_1, \dots, t'_n) \text{typeconstr_name} \\
E \vdash \text{typeconstr_name} \triangleright \text{typeconstr_name} : \text{kind}\{\text{field_name}'_1; \dots; \text{field_name}'_m\} \\
\text{field_name}_1 \dots \text{field_name}_n \textbf{PERMUTES} \text{field_name}'_1 \dots \text{field_name}'_m \\
\text{length}(e_1) \dots (e_n) \geq 1 \\
E \vdash t \equiv t' \\
\hline
\sigma^T \& E \vdash \{\text{field_name}_1 = e_1; \dots; \text{field_name}_n = e_n\} : t' & \text{JTe_record_constr} \\
\sigma^T \& E \vdash \text{expr} : t \\
E \vdash \text{field_name}_1 : t \rightarrow t_1 \dots E \vdash \text{field_name}_n : t \rightarrow t_n \\
\sigma^T \& E \vdash e_1 : t_1 \dots \sigma^T \& E \vdash e_n : t_n \\
\text{field_name}_1 \dots \text{field_name}_n \textbf{distinct} \\
\text{length}(e_1) \dots (e_n) \geq 1 \\
E \vdash t \equiv t' \\
\hline
\sigma^T \& E \vdash \{\text{expr with field_name}_1 = e_1; \dots; \text{field_name}_n = e_n\} : t' & \text{JTe_record_with} \\
\sigma^T \& E \vdash e : t_1 \rightarrow t \\
\sigma^T \& E \vdash e_1 : t_1 \\
\hline
\sigma^T \& E \vdash e e_1 : t & \text{JTe_apply} \\
\sigma^T \& E \vdash e : t \\
E \vdash \text{field_name} : t \rightarrow t' \\
E \vdash t' \equiv t'' \\
\hline
\sigma^T \& E \vdash e.\text{field_name} : t'' & \text{JTe_record_proj} \\
\sigma^T \& E \vdash e_1 : \text{bool} \\
\sigma^T \& E \vdash e_2 : \text{bool} \\
E \vdash \text{bool} \equiv t \\
\hline
\sigma^T \& E \vdash e_1 \& \& e_2 : t & \text{JTe_and} \\
\sigma^T \& E \vdash e_1 : \text{bool} \\
\sigma^T \& E \vdash e_2 : \text{bool} \\
E \vdash \text{bool} \equiv t \\
\hline
\sigma^T \& E \vdash e_1 || e_2 : t & \text{JTe_or} \\
\sigma^T \& E \vdash e_1 : \text{bool} \\
\sigma^T \& E \vdash e_2 : t \\
\sigma^T \& E \vdash e_3 : t \\
\hline
\sigma^T \& E \vdash \text{if } e_1 \text{ then } e_2 \text{ else } e_3 : t & \text{JTe_ifthenelse}
\end{array}$$

$$\begin{array}{c}
\frac{\sigma^T \& E \vdash e_1 : \mathbf{bool} \quad \sigma^T \& E \vdash e_2 : \mathbf{unit} \quad E \vdash \mathbf{unit} \equiv t}{\sigma^T \& E \vdash \mathbf{while } e_1 \mathbf{ do } e_2 \mathbf{ done } : t} \quad \text{JTe_while} \\
\\
\frac{\sigma^T \& E \vdash e_1 : \mathbf{int} \quad \sigma^T \& E \vdash e_2 : \mathbf{int} \quad \sigma^T \& E, \text{lowercase_ident} : \mathbf{int} \vdash e_3 : \mathbf{unit} \quad E \vdash \mathbf{unit} \equiv t}{\sigma^T \& E \vdash \mathbf{for } \text{lowercase_ident} = e_1 \mathbf{ [down]to } e_2 \mathbf{ do } e_3 \mathbf{ done } : t} \quad \text{JTe_for} \\
\\
\frac{\sigma^T \& E \vdash e_1 : \mathbf{unit} \quad \sigma^T \& E \vdash e_2 : t}{\sigma^T \& E \vdash e_1; e_2 : t} \quad \text{JTe_sequence}
\end{array}$$

In the above rule, e_1 must have type **unit**. Ocaml lets the programmer off with a warning, unless `-warn-error S` is passed on the compiler command line.

$$\begin{array}{c}
\frac{\sigma^T \& E \vdash e : t \quad \sigma^T \& E \vdash \text{pattern_matching} : t \rightarrow t'}{\sigma^T \& E \vdash \mathbf{match } e \mathbf{ with } \text{pattern_matching} : t'} \quad \text{JTe_match} \\
\\
\frac{\sigma^T \& E \vdash \text{pattern_matching} : t \rightarrow t' \quad E \vdash t \rightarrow t' \equiv t''}{\sigma^T \& E \vdash \mathbf{function } \text{pattern_matching} : t''} \quad \text{JTe_function} \\
\\
\frac{\sigma^T \& E \vdash e : t \quad \sigma^T \& E \vdash \text{pattern_matching} : \mathbf{exn} \rightarrow t}{\sigma^T \& E \vdash \mathbf{try } e \mathbf{ with } \text{pattern_matching} : t} \quad \text{JTe_try}
\end{array}$$

We give three rules for **let** expressions. The rule **JTe_ilet_imono** describes “monomorphic let”: it does not allow the type of *expr* to be generalised. The rule **JTe_ilet_ipoly** describes “polymorphic let”: it allows any number of type variables in the type of *nexp* to be generalised (more precisely, this generalisation applies simultaneously to the types of all the variables bound by *pat*), at the cost of requiring *nexp* to be non-expansive (which is described syntactically through the grammar for *nexp*). The rule **JTe_iletrec** allows mutually recursive functions to be defined; since immediate functions are values, thus nonexpansive, there is no need for a monomorphic **let rec** rule.

$$\begin{array}{c}
\frac{\sigma^T \& E \vdash pat = expr \triangleright x_1 : t_1, \dots, x_n : t_n \quad \sigma^T \& E @ x_1 : t_1, \dots, x_n : t_n \vdash e : t}{\sigma^T \& E \vdash \mathbf{let } pat = expr \mathbf{ in } e : t} \quad \text{JTe_let_mono} \\
\\
\frac{\mathbf{shift } 0 1 \sigma^T \& E, \mathbf{TV} \vdash pat = nexp \triangleright x_1 : t_1, \dots, x_n : t_n \quad \sigma^T \& E @ x_1 : \forall t_1, \dots, x_n : \forall t_n \vdash e : t}{\sigma^T \& E \vdash \mathbf{let } pat = nexp \mathbf{ in } e : t} \quad \text{JTe_let_poly}
\end{array}$$

$$\begin{array}{c}
 \frac{\text{shift } 0\ 1\ \sigma^T \& E, \mathbf{TV} \vdash \text{letrec_bindings} \triangleright x_1 : t_1, \dots, x_n : t_n}{\sigma^T \& E @ (x_1 : \forall t_1), \dots, (x_n : \forall t_n) \vdash e : t} \quad \text{JTe_letrec} \\
 \frac{\sigma^T \& E \vdash e : \mathbf{bool}}{\frac{E \vdash \mathbf{unit} \equiv t}{\sigma^T \& E \vdash \mathbf{assert} e : t}} \quad \text{JTe_assert} \\
 \frac{E \vdash t : \mathbf{Type}}{\sigma^T \& E \vdash \mathbf{assert false} : t} \quad \text{JTe_assertfalse} \\
 \frac{\begin{array}{c} E \vdash \mathbf{ok} \\ E \vdash \text{location} \triangleright \text{location} : t \\ E \vdash t \ \mathbf{ref} \equiv t' \end{array}}{\sigma^T \& E \vdash \text{location} : t'} \quad \text{JTe_location}
 \end{array}$$

3.25 $\boxed{\sigma^T \& E \vdash \text{pattern_matching} : \text{typexpr} \rightarrow \text{typexpr}'}$ Pattern matching/expression pair typing

Determines the function type of a sequence of pattern/expression pairs. The function type describes the type of the value matched by all of the patterns and the type of the value returned by all of the expressions. σ^T gives the types that should replace type variables in explicitly type-annotated patterns.

$$\frac{\begin{array}{c} \sigma^T \& E \vdash \text{pattern}_1 : t \triangleright E_1 \dots \sigma^T \& E \vdash \text{pattern}_n : t \triangleright E_n \\ \sigma^T \& E @ E_1 \vdash e_1 : t' \dots \sigma^T \& E @ E_n \vdash e_n : t' \\ \mathbf{length}(\text{pattern}_1) \dots (\text{pattern}_n) \geq 1 \end{array}}{\sigma^T \& E \vdash \text{pattern}_1 \rightarrow e_1 | \dots | \text{pattern}_n \rightarrow e_n : t \rightarrow t'} \quad \text{JTpatt_matching_pm}$$

3.26 $\boxed{\sigma^T \& E \vdash \text{let_binding} \triangleright E'}$ Let binding typing

Determines the types bound by a let bindings pattern.

$$\frac{\begin{array}{c} \sigma^T \& E \vdash \text{pattern} : t \triangleright x_1 : t_1, \dots, x_n : t_n \\ \sigma^T \& E \vdash \text{expr} : t \end{array}}{\sigma^T \& E \vdash \text{pattern} = \text{expr} \triangleright (x_1 : t_1), \dots, (x_n : t_n)} \quad \text{JTlet_binding_poly}$$

3.27 $\boxed{\sigma^T \& E \vdash \text{letrec_bindings} \triangleright E'}$ **Recursive let binding typing**

Determines the types bound by a recursive let's patterns (which are always just variables).

$$\frac{E' = E @ \text{value_name}_1 : t_1 \rightarrow t'_1, \dots, \text{value_name}_n : t_n \rightarrow t'_n}{\sigma^T \& E' \vdash \text{pattern_matching}_1 : t_1 \rightarrow t'_1 \dots \sigma^T \& E' \vdash \text{pattern_matching}_n : t_n \rightarrow t'_n} \text{ value_name}_1 \dots \text{value_name}_n \text{ distinct}$$

$$\frac{\sigma^T \& E \vdash \text{value_name}_1 = \mathbf{function} \text{ pattern_matching}_1 \mathbf{and} \dots \mathbf{and} \text{value_name}_n = \mathbf{function} \text{ pattern_matching}_n \triangleright \text{value_name}_1 : t_1 \rightarrow t'_1, \dots, \text{value_name}_n : t_n \rightarrow t'_n}{\text{JTletrec_binding_equal_function}}$$

3.28 $\boxed{\text{type_params_opt typeconstr} \vdash \text{constr_decl} \triangleright EB}$ **Variant constructor declaration**

Collects the constructors of a variant type declaration using named type schemes for the type parameters.

$$\frac{}{(\alpha_1, \dots, \alpha_n) \text{ typeconstr} \vdash \text{constr_name} \triangleright \text{constr_name of typeconstr}} \text{ JTconstr_decl_nullary}$$

$$\frac{}{(\alpha_1, \dots, \alpha_n) \text{ typeconstr} \vdash \text{constr_name of } t_1 * \dots * t_n \triangleright \text{constr_name of } \forall (\alpha_1, \dots, \alpha_n), (t_1, \dots, t_n) : \text{typeconstr}} \text{ JTconstr_decl_nary}$$

3.29 $\boxed{\text{type_params_opt typeconstr_name} \vdash \text{field_decl} \triangleright EB}$ **Record field declaration**

Collects the fields of a record type using named type schemes for the type parameters.

$$\frac{}{(\alpha_1, \dots, \alpha_n) \text{ typeconstr_name} \vdash fn : t \triangleright fn : \forall (\alpha_1, \dots, \alpha_n), \text{typeconstr_name} \rightarrow t} \text{ JTfield_decl_only}$$

3.30 $\boxed{\vdash \text{typedef}_1 \mathbf{and} \dots \mathbf{and} \text{typedef}_n \triangleright E' \mathbf{and} E'' \mathbf{and} E'''}$ **Type definitions collection**

A type definition declares several sorts of names: type constructors (some of them corresponding to freshly generated types, others to type abbreviations), and data constructors and destructors. These names are collected into three environments:

- E' contains generative type definitions (variant and record types);

- E'' contains type abbreviations;
- E''' contains constructors and destructors for generative datatypes.

The order E' , E'' , E''' is chosen so that their concatenation is well-formed, because no component may refer to a subsequent one. The first component E' , only contains declarations of names which do not depend on anything. The second component E'' contains type abbreviations topologically sorted according to their dependency order, which is possible since we do not allow recursive type abbreviations (in Objective Caml, without the `-rectypes` compiler option, recursive type abbreviations are only allowed when guarded polymorphic variants and object types) — recursive types must be guarded by a generative datatype. Finally E''' declares constructors and destructors for the types declared in E' ; E''' may refer to types declared in E' or E'' in the types of the arguments to these constructors and destructors.

This judgement form does not directly assert the correctness of the definitions: this is performed by the rule $\text{JTtype}\text{definition}\text{list}$ below, which states that the environment assembled here must be well-formed.

$$\begin{array}{c}
 \frac{}{\vdash \triangleright \text{empty and empty and empty}} \text{JTtypedef_empty} \\
 \\
 \frac{\vdash \overline{\text{typedef}_i}^i \triangleright E \text{ and } E' \text{ and } E''}{\vdash \text{type_params_opt typeconstr_name} = t \text{ and } \overline{\text{typedef}_i}^i \triangleright E \text{ and } E', (\text{type_params_opt typeconstr_name} = t) \text{ and } E''} \text{JTtypedef_eq} \\
 \\
 \frac{\begin{array}{c} \vdash \overline{\text{typedef}_i}^i \triangleright E \text{ and } E' \text{ and } E'' \\ \vdash \text{type_params_opt} : \text{kind} \\ \text{type_params_opt typeconstr_name} \vdash \text{constr_decl}_1 \triangleright EB_1 \dots \text{type_params_opt typeconstr_name} \vdash \text{constr_decl}_n \triangleright EB_n \end{array}}{\begin{array}{c} \vdash \text{type_params_opt typeconstr_name} = \text{constr_decl}_1 | \dots | \text{constr_decl}_n \text{ and } \overline{\text{typedef}_i}^i \triangleright \\ E, (\text{typeconstr_name} : \text{kind}) \text{ and } E' \text{ and } E'' @ EB_1, \dots, EB_n \end{array}} \text{JTtypedef_def_sum} \\
 \\
 \frac{\begin{array}{c} \vdash \overline{\text{typedef}_i}^i \triangleright E \text{ and } E' \text{ and } E'' \\ \vdash \text{type_params_opt} : \text{kind} \\ \text{type_params_opt typeconstr_name} \vdash \text{field_name}_1 : t_1 \triangleright EB_1 \dots \text{type_params_opt typeconstr_name} \vdash \text{field_name}_n : t_n \triangleright EB_n \end{array}}{\begin{array}{c} \vdash \text{type_params_opt typeconstr_name} = \{\text{field_name}_1 : t_1; \dots; \text{field_name}_n : t_n\} \text{ and } \overline{\text{typedef}_i}^i \triangleright \\ E, (\text{typeconstr_name} : \text{kind}\{\text{field_name}_1; \dots; \text{field_name}_n\}) \text{ and } E' \text{ and } E'' @ EB_1, \dots, EB_n \end{array}} \text{JTtypedef_def_record}
 \end{array}$$

A variant type definition yields two sorts of bindings: one for the type constructor name and one for each constructor.

$$\frac{\begin{array}{c} \vdash \overline{\text{typedef}_i}^i \triangleright E \text{ and } E' \text{ and } E'' \\ \vdash \text{type_params_opt} : \text{kind} \\ \text{type_params_opt typeconstr_name} \vdash \text{field_name}_1 : t_1 \triangleright EB_1 \dots \text{type_params_opt typeconstr_name} \vdash \text{field_name}_n : t_n \triangleright EB_n \end{array}}{\begin{array}{c} \vdash \text{type_params_opt typeconstr_name} = \{\text{field_name}_1 : t_1; \dots; \text{field_name}_n : t_n\} \text{ and } \overline{\text{typedef}_i}^i \triangleright \\ E, (\text{typeconstr_name} : \text{kind}\{\text{field_name}_1; \dots; \text{field_name}_n\}) \text{ and } E' \text{ and } E'' @ EB_1, \dots, EB_n \end{array}} \text{JTtypedef_def_record}$$

A record type definition yields two sorts of bindings: one for the type constructor name and one for each field. The field names are also recorded with the type constructor binding; this information is used in the rule $\text{JTe}\text{record}\text{constr}$ to make sure that record expressions specify all fields. (We would similarly tag type constructor bindings for variant types with their constructor names if we wanted to check the exhaustivity of pattern matching.)

3.31 $E \vdash \text{type_definition} \triangleright E'$ Type definition well-formedness and binding collection

Collects the bindings of a type definition and ensures that they are well-formed. Any given name may be defined at most once, and all names used must have been bound previously or earlier in the same type definition phrase. The conditions are checked by the premise $E @ E''' \vdash \text{ok}$ in the rule $\text{JTtype_definition_list}$ and the assembly is performed by the type definitions collection rules above. This implies that the type abbreviations must be topologically sorted in their dependency order. (Generative type definitions are exempt from such constraints.) Programmers do not have to abide by this constraint: they may order type abbreviations in any way. Therefore the rule $\text{JTtype_definition_swap}$ allows an arbitrary reordering of type definitions — it suffices for a type definition to be correct that there exist a reordering that makes the type abbreviations properly ordered.

$$\frac{\begin{array}{c} \vdash \text{typedef}_1 \text{ and } \dots \text{ and } \text{typedef}_n \triangleright E' \text{ and } E'' \text{ and } E''' \\ E''' = E' @ E'' @ E''' \\ E @ E''' \vdash \text{ok} \end{array}}{E \vdash \text{type } \text{typedef}_1 \text{ and } \dots \text{ and } \text{typedef}_n \triangleright E'''} \quad \text{JTtype_definition_list}$$

$$\frac{E \vdash \text{type } \overline{\text{typedef}_i}^i \text{ and } \text{typedef}' \text{ and } \text{typedef} \text{ and } \overline{\text{typedef}_j''}^j \triangleright E'}{E \vdash \text{type } \overline{\text{typedef}_i}^i \text{ and } \text{typedef} \text{ and } \text{typedef}' \text{ and } \overline{\text{typedef}_j''}^j \triangleright E'} \quad \text{JTtype_definition_swap}$$

3.32 $E \vdash \text{definition} : E'$ Definition typing

Collects the bindings of a definition and ensures that they are well-formed. Each definition can bind zero, one or more names. Type variables that are mentioned by the programmer in type annotations are scoped at this level. Thus, the σ^T substitution is arbitrarily created for each definition to ensure that each type variable is used consistently in the definition.

$$\frac{\sigma^T \& E, \mathbf{TV} \vdash pat = nexp \triangleright (x_1 : t'_1), \dots, (x_k : t'_k)}{E \vdash \text{let } pat = nexp : (x_1 : \forall t'_1), \dots, (x_k : \forall t'_k)} \quad \text{JTdefinition_let_poly}$$

$$\frac{\sigma^T \& E \vdash pat = expr \triangleright (x_1 : t'_1), \dots, (x_k : t'_k)}{E \vdash \text{let } pat = expr : (x_1 : t'_1), \dots, (x_k : t'_k)} \quad \text{JTdefinition_let_mono}$$

$$\frac{\sigma^T \& E, \mathbf{TV} \vdash letrec_bindings \triangleright (x_1 : t'_1), \dots, (x_k : t'_k)}{E \vdash \text{let rec } letrec_bindings : (x_1 : \forall t'_1), \dots, (x_k : \forall t'_k)} \quad \text{JTdefinition_letrec}$$

$$\frac{E \vdash \text{type } \text{typedef}_1 \text{ and } \dots \text{ and } \text{typedef}_n \triangleright E'}{E \vdash \text{type } \text{typedef}_1 \text{ and } \dots \text{ and } \text{typedef}_n : E'} \quad \text{JTdefinition_typedef}$$

$$\frac{\begin{array}{c} E \vdash \text{ok} \\ \mathbf{exn} \vdash constr_decl \triangleright EB \end{array}}{E \vdash \text{exception } constr_decl : EB} \quad \text{JTdefinition_exndef}$$

3.33 $E \vdash definitions : E'$ Definition sequence typing

Collects the bindings of a definition and ensures that they are well-typed.

$$\frac{E \vdash \text{ok}}{E \vdash :} \quad \text{JTdefinitions_empty}$$

$$\frac{\begin{array}{c} E \vdash definition : E' \\ E @ E' \vdash definitions' : E'' \end{array}}{E \vdash definition definitions' : E' @ E''} \quad \text{JTdefinitions_item}$$

3.34 $E \vdash program : E'$ Program typing

Checks a program.

$$\frac{E \vdash definitions : E'}{E \vdash definitions : E'} \quad \text{JTprog_defs}$$

$$\frac{\sigma^T \& E \vdash v : t}{E \vdash (\%primraise)v :} \quad \text{JTprog_raise}$$

3.35 $E \vdash store : E'$ Store typing

Checks that the values in a store have types.

$$\frac{}{E \vdash \text{empty} :} \quad \text{JTstore_empty}$$

$$\frac{\begin{array}{c} E \vdash store : E' \\ \{\} \& E \vdash v : t \end{array}}{E \vdash store, l \mapsto v : E', (l : t)} \quad \text{JTstore_map}$$

3.36 $E \vdash \langle program, store \rangle$ Top-level typing

Checks the combination of a program with a store. The store is typed in an environment that includes its bindings, so that it can contain cyclic structures.

$$\frac{E @ E' \vdash store : E' \quad E @ E' \vdash program : E''}{E \vdash \langle program, store \rangle} \text{ JTtop_defs}$$

3.37 $\sigma^T \& E \vdash L$ Label-to-environment extraction

Used in the proof only

$$\frac{}{\sigma^T \& E \vdash} \text{ JTLin_nil}$$

$$\frac{\text{dom}(E) \triangleright names \quad location \notin names}{\sigma^T \& E \vdash \text{ref } v = location} \text{ JTLin_alloc}$$

$$\frac{\sigma^T \& E \vdash v : t \quad E \vdash location \triangleright (location : t)}{\sigma^T \& E \vdash !location = v} \text{ JTLin_deref}$$

$$\frac{}{\sigma^T \& E \vdash location := v} \text{ JTLin_assign}$$

3.38 $\sigma^T \& E \vdash L \triangleright E'$ Label-to-environment extraction

Used in the proof only

$$\frac{}{\sigma^T \& E \vdash \triangleright} \text{ JTLoc_nil}$$

$$\frac{\sigma^T \& E \vdash v : t}{\sigma^T \& E \vdash \text{ref } v = location \triangleright (location : t)} \text{ JTLoc_alloc}$$

$$\frac{}{\sigma^T \& E \vdash !location = v \triangleright} \text{ JTLoc_deref}$$

$$\frac{\sigma^T \& E \vdash v : t \quad E \vdash location \triangleright (location : t)}{\sigma^T \& E \vdash location := v \triangleright} \text{ JTLoc_assign}$$

4 Operational Semantics

The operational semantics is a labelled transition system that lifts imperative and non-deterministic behavior our of the core evaluation rules. Notable aspects of the formalization include:

- explicit rules for evaluation in context (instead of a grammar of evaluation contexts),
- small-step propagation of exceptions,
- substitution-based function application,
- right-to-left evaluation ordering, which is overspecified compared to the OCaml manual; furthermore, this choice of evaluation ordering for record expressions differs from the implementation's choice, which is based on the type declaration,
- unlike the implementation, we do not treat curried functions specially, the difference can be seen in this program: `let f = function1 → function_- → 10; let _ = f 2;`; which does not raise an exception in the implementation.
- As in the type system, several rules have premises that state there are at least 1 (or 2) elements of a list, despite there being 3 or 4 dots. This is because Ott does not use dot imposed length restrictions in the theorem prover models.

4.1 $\vdash \text{expr matches pattern}$ Pattern matching

Determines if a value matches a pattern.

$$\begin{array}{c}
 \frac{}{\vdash v \text{ matches } x} \text{ JM_matchP_var} \\
 \frac{}{\vdash v \text{ matches } _} \text{ JM_matchP_any} \\
 \frac{}{\vdash \text{constant matches constant}} \text{ JM_matchP_constant} \\
 \frac{\vdash v \text{ matches } pat}{\vdash v \text{ matches } pat \text{ as } x} \text{ JM_matchP_alias} \\
 \frac{\vdash v \text{ matches } pat}{\vdash v \text{ matches } (pat : t)} \text{ JM_matchP_typed} \\
 \frac{\vdash v \text{ matches } pat_1}{\vdash v \text{ matches } pat_1 | pat_2} \text{ JM_matchP_or_left} \\
 \frac{\vdash v \text{ matches } pat_2}{\vdash v \text{ matches } pat_1 | pat_2} \text{ JM_matchP_or_right}
 \end{array}$$

$$\begin{array}{c}
\frac{\vdash v_1 \text{ matches } pat_1 \dots \vdash v_n \text{ matches } pat_n}{\vdash constr(v_1, \dots, v_n) \text{ matches } constr(pat_1, \dots, pat_n)} \quad \text{JM_matchP_construct} \\[10pt]
\frac{\vdash constr(v_1, \dots, v_n) \text{ matches } constr_-}{\vdash constr(v_1, \dots, v_n) \text{ matches } constr_-} \quad \text{JM_matchP_construct_any} \\[10pt]
\frac{\vdash v_1 \text{ matches } pat_1 \dots \vdash v_n \text{ matches } pat_n}{\vdash (v_1, \dots, v_n) \text{ matches } (pat_1, \dots, pat_n)} \quad \text{JM_matchP_tuple} \\[10pt]
\frac{\begin{array}{l} field_name'_1 = v'_1 \dots field_name'_n = v'_n \\ fn_1 = v''_1 \dots fn_l = v''_l \end{array} \text{ PERMUTES } field_name_1 = v_1 \dots field_name_m = v_m}{\begin{array}{l} \vdash v'_1 \text{ matches } pat_1 \dots \vdash v'_n \text{ matches } pat_n \\ field_name_1 \dots field_name_m \text{ distinct} \end{array}} \quad \text{JM_matchP_record} \\[10pt]
\frac{\begin{array}{l} \vdash v_1 \text{ matches } pat_1 \\ \vdash v_2 \text{ matches } pat_2 \end{array}}{\vdash v_1 :: v_2 \text{ matches } pat_1 :: pat_2} \quad \text{JM_matchP_cons}
\end{array}$$

4.2 $\vdash expr \text{ matches } pattern \triangleright \{substs_x\}$ Pattern matching with substitution creation

Determines if a value matches a pattern and destructures the value into a substitution according to the pattern's variables. The previous pattern matching relation is used to get deterministic behavior for \mid patterns.

$$\begin{array}{c}
\frac{}{\vdash v \text{ matches } x \triangleright \{x \leftarrow v\}} \quad \text{JM_match_var} \\[10pt]
\frac{}{\vdash v \text{ matches } _- \triangleright \{\}} \quad \text{JM_match_any} \\[10pt]
\frac{}{\vdash constant \text{ matches } constant \triangleright \{\}} \quad \text{JM_match_constant} \\[10pt]
\frac{\vdash v \text{ matches } pat \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}}{\vdash v \text{ matches } pat \text{ as } x \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n, x \leftarrow v\}} \quad \text{JM_match_alias} \\[10pt]
\frac{\vdash v \text{ matches } pat \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}}{\vdash v \text{ matches } (pat : t) \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}} \quad \text{JM_match_typed} \\[10pt]
\frac{\vdash v \text{ matches } pat_1 \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}}{\vdash v \text{ matches } pat_1 | pat_2 \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}} \quad \text{JM_match_or_left}
\end{array}$$

$$\begin{array}{c}
\frac{\neg(v \text{ matches } pat_1) \quad \vdash v \text{ matches } pat_2 \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}}{\vdash v \text{ matches } pat_1 | pat_2 \triangleright \{x_1 \leftarrow v_1, \dots, x_n \leftarrow v_n\}} \quad \text{JM_match_or_right} \\
\frac{\vdash v_1 \text{ matches } pat_1 \triangleright \{substs_x_1\} \quad \dots \quad \vdash v_n \text{ matches } pat_n \triangleright \{substs_x_n\}}{\vdash constr(v_1, \dots, v_n) \text{ matches } constr(pat_1, \dots, pat_n) \triangleright \{substs_x_1 @ \dots @ substs_x_n\}} \quad \text{JM_match_construct} \\
\frac{}{\vdash constr(v_1, \dots, v_n) \text{ matches } constr_ \triangleright \{\}} \quad \text{JM_match_construct_any} \\
\frac{\vdash v_1 \text{ matches } pat_1 \triangleright \{substs_x_1\} \quad \dots \quad \vdash v_n \text{ matches } pat_n \triangleright \{substs_x_n\}}{\vdash (v_1, \dots, v_n) \text{ matches } (pat_1, \dots, pat_n) \triangleright \{substs_x_1 @ \dots @ substs_x_n\}} \quad \text{JM_match_tuple} \\
\frac{field_name'_1 = v'_1 \dots field_name'_n = v'_n \quad fn_1 = v''_1 \dots fn_l = v''_l \quad \text{PERMUTES} \quad field_name_1 = v_1 \dots field_name_m = v_m \quad \vdash v'_1 \text{ matches } pat_1 \triangleright \{substs_x_1\} \quad \dots \quad \vdash v'_n \text{ matches } pat_n \triangleright \{substs_x_n\} \quad field_name_1 \dots field_name_m \text{ distinct}}{\vdash \{field_name_1 = v_1; \dots; field_name_m = v_m\} \text{ matches } \{field_name'_1 = pat_1; \dots; field_name'_n = pat_n\} \triangleright \{substs_x_1 @ \dots @ substs_x_n\}} \quad \text{JM_match_record} \\
\frac{\vdash v_1 \text{ matches } pat_1 \triangleright \{substs_x_1\} \quad \vdash v_2 \text{ matches } pat_2 \triangleright \{substs_x_2\}}{\vdash v_1 :: v_2 \text{ matches } pat_1 :: pat_2 \triangleright \{substs_x_1 @ substs_x_2\}} \quad \text{JM_match_cons}
\end{array}$$

4.3 recfun (letrec_bindings, pattern_matching) \triangleright expr Recursive function helper

Expands a recursive definition.

$$\frac{letrec_bindings = (x_1 = \text{function } pattern_matching_1 \text{ and } \dots \text{ and } x_n = \text{function } pattern_matching_n)}{\text{recfun} (letrec_bindings, pattern_matching) \triangleright \{x_1 \leftarrow \text{let rec letrec_bindings in } x_1, \dots, x_n \leftarrow \text{let rec letrec_bindings in } x_n\} (\text{function } pattern_matching)} \quad \text{Jrecfun_letrec}$$

4.4 funval (e) Function values

Determines if an expression is a function value, for use in (Jbprim_equal_fun).

$$\frac{}{\vdash \text{funval} ((\%prim unary_prim))} \quad \text{Jfunval_up} \\
\frac{}{\vdash \text{funval} ((\%prim binary_prim))} \quad \text{Jfunval_bp}$$

$$\frac{}{\vdash \text{funval}((\% \text{prim} \text{binary_prim}) v)} \text{Jfunval_bp_app}$$

$$\frac{}{\vdash \text{funval}(\text{function pattern_matching})} \text{Jfunval_func}$$

4.5 $\boxed{\vdash \text{unary_prim} \text{expr} \xrightarrow{L} \text{expr}'}$ **Unary primitive evaluation**

Computes the result of a unary primitive application.

$$\frac{}{\vdash \text{not true} \longrightarrow \text{false}} \text{Juprim_not_true}$$

$$\frac{}{\vdash \text{not false} \longrightarrow \text{true}} \text{Juprim_not_false}$$

$$\frac{}{\vdash \sim \dot{n} \longrightarrow 0 \dot{-} \dot{n}} \text{Juprim_uminus}$$

The effect of creating a reference is communicated to the store via the label on the reduction arrow. Similarly the reduction arrow carries the value read from the store when accessing a location.

$$\frac{}{\vdash \text{ref } v \xrightarrow{\text{ref } v = l} l} \text{Juprim_ref_alloc}$$

$$\frac{}{\vdash !l \xrightarrow{!l = v} v} \text{Juprim_deref}$$

4.6 $\boxed{\vdash \text{expr}_1 \text{binary_prim} \text{expr}_2 \xrightarrow{L} \text{expr}}$ **Binary primitive evaluation**

Computes the result of a binary primitive application.

$$\frac{\vdash \text{funval}(v)}{\vdash v = v' \longrightarrow (\% \text{primraise})(\text{Invalid_argument}(\text{equal_error_string}))} \text{Jbprim_equal_fun}$$

$$\frac{\vdash \text{constant} = \text{constant} \longrightarrow \text{true}}{\vdash \text{constant} \neq \text{constant}'} \text{Jbprim_equal_const_true}$$

$$\frac{\vdash \text{constant} = \text{constant}' \longrightarrow \text{false}}{\vdash \text{constant} = \text{constant}' \longrightarrow \text{false}} \text{Jbprim_equal_const_false}$$

$$\frac{}{\vdash l = l' \longrightarrow ((\% \text{prim} =) ((\% \text{prim}!) l)) ((\% \text{prim}!) l')} \text{Jbprim_equal_loc}$$

$$\begin{array}{c}
\frac{}{\vdash (v_1 :: v_2) = (v'_1 :: v'_2) \longrightarrow (((\%prim =) v_1) v'_1) \& \& (((\%prim =) v_2) v'_2)} \text{Jbprim_equal_cons} \\
\frac{}{\vdash (v_1 :: v_2) = [] \longrightarrow \mathbf{false}} \text{Jbprim_equal_cons_nil} \\
\frac{}{\vdash [] = (v_1 :: v_2) \longrightarrow \mathbf{false}} \text{Jbprim_equal_nil_cons} \\
\frac{\text{length}(v_1) \dots (v_n) \geq 2}{\vdash (v_1, \dots, v_n) = (v'_1, \dots, v'_n) \longrightarrow \mathbf{AND} (((\%prim =) v_1) v'_1 \& \& \dots \& \& ((\%prim =) v_n) v'_n)} \text{Jbprim_equal_tuple} \\
\frac{}{\vdash (constr(v_1, \dots, v_n)) = (constr(v'_1, \dots, v'_n)) \longrightarrow \mathbf{AND} (((\%prim =) v_1) v'_1 \& \& \dots \& \& ((\%prim =) v_n) v'_n)} \text{Jbprim_equal_constr} \\
\frac{constr \neq constr'}{\vdash constr(v_1, \dots, v_m) = constr'(v'_1, \dots, v'_n) \longrightarrow \mathbf{false}} \text{Jbprim_equal_constr_false} \\
\frac{}{\vdash constr' = constr(v_1, \dots, v_n) \longrightarrow \mathbf{false}} \text{Jbprim_equal_const_constr_false} \\
\frac{}{\vdash constr(v_1, \dots, v_n) = constr' \longrightarrow \mathbf{false}} \text{Jbprim_equal_constr_const_false} \\
\frac{v' = \{fn''_1 = v''_1; \dots; fn''_m = v''_m\} \\ fn_1 \dots fn_n \mathbf{PERMUTES} fn''_1 \dots fn''_m}{\vdash \{fn_1 = v_1; \dots; fn_n = v_n\} = v' \longrightarrow \mathbf{AND} (((\%prim =) v_1) (v'.fn_1) \& \& \dots \& \& ((\%prim =) v_n) (v'.fn_n))} \text{Jbprim_equal_rec} \\
\frac{}{\vdash \dot{n}_1 + \dot{n}_2 \longrightarrow \dot{n}_1 + \dot{n}_2} \text{Jbprim_plus} \\
\frac{}{\vdash \dot{n}_1 - \dot{n}_2 \longrightarrow \dot{n}_1 - \dot{n}_2} \text{Jbprim_minus} \\
\frac{}{\vdash \dot{n}_1 * \dot{n}_2 \longrightarrow \dot{n}_1 * \dot{n}_2} \text{Jbprim_times} \\
\frac{}{\vdash \dot{n} / 0 \longrightarrow (\%primraise) \mathbf{Division_by_zero}} \text{Jbprim_div0} \\
\frac{\dot{n}_2 \neq 0}{\vdash \dot{n}_1 / \dot{n}_2 \longrightarrow \dot{n}_1 / \dot{n}_2} \text{Jbprim_div}
\end{array}$$

The side effect of an assignment is communicated to the store via the label on the reduction arrow.

$$\frac{}{\vdash l := v \xrightarrow{l:=v} ()} \text{Jbprim_assign}$$

4.7 $\boxed{\vdash \text{expr with pattern_matching} \longrightarrow \text{pattern_matching}'}$ **Pattern matching step**

Proceeding to the next case because the first, but not only, case has failed to match.

$$\frac{\neg(v \text{ matches } pat) \quad \text{length}(e_1) \dots (e_n) \geq 1}{\vdash v \text{ with } pat \rightarrow e | pat_1 \rightarrow e_1 | \dots | pat_n \rightarrow e_n \longrightarrow pat_1 \rightarrow e_1 | \dots | pat_n \rightarrow e_n} \text{ JRmatching_next}$$

4.8 $\boxed{\vdash \text{expr with pattern_matching} \longrightarrow \text{expr}'}$ **Pattern matching finished**

Proceeding to an expression because the first case matches, or the only case does not match.

$$\frac{\vdash v \text{ matches } pat \triangleright \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\}}{\vdash v \text{ with } pat \rightarrow e | pat_1 \rightarrow e_1 | \dots | pat_n \rightarrow e_n \longrightarrow \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\} e} \text{ JRmatching_found}$$

$$\frac{\neg(v \text{ matches } pat)}{\vdash v \text{ with } pat \rightarrow e \longrightarrow (\% \text{primraise}) \text{Match_failure}} \text{ JRmatching_fail}$$

4.9 $\boxed{\vdash \text{expr} \xrightarrow{L} \text{expr}'}$ **Expression evaluation**

Reduces an expression one-step. Most evaluation contexts require two rules, one for normal evaluation and one for exception propagation.

$$\frac{\vdash \text{unary_prim } v \xrightarrow{L} e}{\vdash (\% \text{prim unary_prim}) v \xrightarrow{L} e} \text{ JR_expr_uprim}$$

$$\frac{\vdash v_1 \text{ binary_prim } v_2 \xrightarrow{L} e}{\vdash ((\% \text{prim binary_prim}) v_1) v_2 \xrightarrow{L} e} \text{ JR_expr_bprim}$$

$$\frac{}{\vdash (e : t) \longrightarrow e} \text{ JR_expr_typed_ctx}$$

Right-to-left evaluation order for application (i.e., argument before function).

$$\frac{\vdash e_0 \xrightarrow{L} e'_0}{\vdash e_1 e_0 \xrightarrow{L} e_1 e'_0} \text{ JR_expr_apply_ctx_arg}$$

$$\begin{array}{c}
\frac{}{\vdash e ((\% \text{primraise}) v) \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_apply_raise1} \\
\\
\frac{\vdash e_1 \xrightarrow{L} e'_1 \quad \vdash e_1 v_0 \xrightarrow{L} e'_1 v_0}{\vdash e_1 v_0 \xrightarrow{L} e'_1 v_0} \quad \text{JR_expr_apply_ctx_fun} \\
\\
\frac{}{\vdash ((\% \text{primraise}) v) v' \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_apply_raise2} \\
\\
\frac{\vdash (\text{function } \text{pattern_matching } v_0) \longrightarrow \text{match } v_0 \text{ with } \text{pattern_matching}}{\vdash \text{let } pat = e_0 \text{ in } e \xrightarrow{L} \text{let } pat = e'_0 \text{ in } e} \quad \text{JR_expr_apply} \\
\\
\frac{\vdash e_0 \xrightarrow{L} e'_0}{\vdash \text{let } pat = e_0 \text{ in } e \xrightarrow{L} \text{let } pat = e'_0 \text{ in } e} \quad \text{JR_expr_let_ctx} \\
\\
\frac{\vdash \text{let } pat = (\% \text{primraise}) v \text{ in } e \longrightarrow (\% \text{primraise}) v}{\vdash v \text{ matches } pat \triangleright \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\} \quad \vdash \text{let } pat = v \text{ in } e \longrightarrow \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\} e} \quad \text{JR_expr_let_raise} \\
\\
\frac{\vdash \text{let } pat = v \text{ in } e \longrightarrow \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\} e}{\vdash \neg(v \text{ matches } pat) \quad \vdash \text{let } pat = v \text{ in } e \longrightarrow (\% \text{primraise}) \text{ Match_failure}} \quad \text{JR_expr_let_subst} \\
\\
\frac{\vdash \neg(v \text{ matches } pat)}{\vdash \text{let } pat = v \text{ in } e \longrightarrow (\% \text{primraise}) \text{ Match_failure}} \quad \text{JR_expr_let_fail} \\
\\
\frac{\text{letrec_bindings} = (x_1 = \text{function } \text{pattern_matching}_1 \text{ and } \dots \text{ and } x_n = \text{function } \text{pattern_matching}_n) \quad \text{recfun}(\text{letrec_bindings}, \text{pattern_matching}_1) \triangleright e_1 \dots \text{ recfun}(\text{letrec_bindings}, \text{pattern_matching}_n) \triangleright e_n}{\vdash \text{let rec letrec_bindings in } e \longrightarrow \{x_1 \leftarrow e_1, \dots, x_n \leftarrow e_n\} e} \quad \text{JR_expr_letrec} \\
\\
\frac{\vdash e_1 \xrightarrow{L} e'_1}{\vdash e_1; e_2 \xrightarrow{L} e'_1; e_2} \quad \text{JR_expr_sequence_ctx_left} \\
\\
\frac{}{\vdash ((\% \text{primraise}) v); e \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_sequence_raise} \\
\\
\frac{\vdash v; e_2 \longrightarrow e_2}{\vdash e_1 \xrightarrow{L} e'_1} \quad \text{JR_expr_sequence} \\
\\
\frac{\vdash e_1 \xrightarrow{L} e'_1}{\vdash \text{if } e_1 \text{ then } e_2 \text{ else } e_3 \xrightarrow{L} \text{if } e'_1 \text{ then } e_2 \text{ else } e_3} \quad \text{JR_expr_ifthenelse_ctx} \\
\\
\frac{\vdash \text{if } (\% \text{primraise}) v \text{ then } e_1 \text{ else } e_2 \longrightarrow (\% \text{primraise}) v}{\vdash \text{if true then } e_2 \text{ else } e_3 \longrightarrow e_2} \quad \text{JR_expr_if_raise} \\
\\
\frac{\vdash \text{if true then } e_2 \text{ else } e_3 \longrightarrow e_2}{\vdash \text{if true then } e_2 \text{ else } e_3 \longrightarrow e_2} \quad \text{JR_expr_ifthenelse_true}
\end{array}$$

$$\frac{}{\vdash \text{if false then } e_2 \text{ else } e_3 \rightarrow e_3} \text{JR_expr_ifthenelse_false}$$

We treat matching one pattern against one value as atomic (this would be relevant when matching the contents of a reference after introducing concurrent evaluation).

$$\begin{array}{c} \frac{}{\vdash e \xrightarrow{L} e'} \text{JR_expr_match_ctx} \\ \frac{}{\vdash \text{match } e \text{ with } \text{pattern_matching} \xrightarrow{L} \text{match } e' \text{ with } \text{pattern_matching}} \text{JR_expr_match_raise} \\ \frac{}{\vdash v \text{ with } \text{pattern_matching} \rightarrow \text{pattern_matching}'} \text{JR_expr_match_step} \\ \frac{\vdash v \text{ with } \text{pattern_matching} \rightarrow e'}{\vdash \text{match } v \text{ with } \text{pattern_matching} \rightarrow e'} \text{JR_expr_match_success} \\ \frac{}{\vdash e_1 \& \& e_2 \rightarrow \text{if } e_1 \text{ then } e_2 \text{ else false}} \text{JR_expr_and} \\ \frac{}{\vdash e_1 \parallel e_2 \rightarrow \text{if } e_1 \text{ then true else } e_2} \text{JR_expr_or} \\ \frac{}{\vdash \text{while } e_1 \text{ do } e_2 \text{ done} \rightarrow \text{if } e_1 \text{ then } (e_2; \text{while } e_1 \text{ do } e_2 \text{ done})} \text{JR_expr_while} \end{array}$$

We specify the evaluation of e_1 before e_2 in **for** loops, which appears to follow the implementation.

$$\begin{array}{c} \frac{}{\vdash e_1 \xrightarrow{L} e'_1} \text{JR_expr_for_ctx1} \\ \frac{}{\vdash \text{for } x = e_1 \text{ [down]to } e_2 \text{ do } e_3 \text{ done} \xrightarrow{L} \text{for } x = e'_1 \text{ [down]to } e_2 \text{ do } e_3 \text{ done}} \text{JR_expr_for_raise1} \\ \frac{}{\vdash \text{for } x = (\%primraise) v \text{ [down]to } e_2 \text{ do } e_3 \text{ done} \rightarrow (\%primraise) v} \text{JR_expr_for_raise1} \\ \frac{\vdash e_2 \xrightarrow{L} e'_2}{\vdash \text{for } x = v_1 \text{ [down]to } e_2 \text{ do } e_3 \text{ done} \xrightarrow{L} \text{for } x = v_1 \text{ [down]to } e'_2 \text{ do } e_3 \text{ done}} \text{JR_expr_for_ctx2} \\ \frac{}{\vdash \text{for } x = v \text{ [down]to } (\%primraise) v' \text{ do } e_3 \text{ done} \rightarrow (\%primraise) v'} \text{JR_expr_for_raise2} \\ \frac{\dot{n}_1 \leq \dot{n}_2}{\vdash \text{for } x = \dot{n}_1 \text{ to } \dot{n}_2 \text{ do } e \text{ done} \rightarrow (\text{let } x = \dot{n}_1 \text{ in } e); \text{for } x = \dot{n}_1 + 1 \text{ to } \dot{n}_2 \text{ do } e \text{ done}} \text{JR_expr_for_to_do} \end{array}$$

$$\begin{array}{c}
\frac{\dot{n_1} > \dot{n_2}}{\vdash \text{for } x = \dot{n_1} \text{ to } \dot{n_2} \text{ do } e \text{ done} \longrightarrow ()} \quad \text{JR_expr_for_to_done} \\
\\
\frac{\dot{n_2} \leq \dot{n_1}}{\vdash \text{for } x = \dot{n_1} \text{ downto } \dot{n_2} \text{ do } e \text{ done} \longrightarrow (\text{let } x = \dot{n_1} \text{ in } e); \text{for } x = \dot{n_1} - 1 \text{ downto } \dot{n_2} \text{ do } e \text{ done}} \quad \text{JR_expr_for_downto_do} \\
\\
\frac{\dot{n_2} > \dot{n_1}}{\vdash \text{for } x = \dot{n_1} \text{ downto } \dot{n_2} \text{ do } e \text{ done} \longrightarrow ()} \quad \text{JR_expr_for_downto_done} \\
\\
\frac{\vdash e \xrightarrow{L} e'}{\vdash \text{try } e \text{ with } \text{pattern_matching} \xrightarrow{L} \text{try } e' \text{ with } \text{pattern_matching}} \quad \text{JR_expr_try_ctx} \\
\\
\frac{\vdash \text{try } v \text{ with } \text{pattern_matching} \longrightarrow v}{\vdash \text{try } v \text{ with } \text{pattern_matching} \longrightarrow v} \quad \text{JR_expr_try_return} \\
\\
\frac{}{\vdash \text{try } (\% \text{primraise}) v \text{ with } \text{pat_exp}_1 | \dots | \text{pat_exp}_n \longrightarrow \text{match } v \text{ with } \text{pat_exp}_1 | \dots | \text{pat_exp}_n | \rightarrow ((\% \text{primraise}) v)} \quad \text{JR_expr_try_catch}
\end{array}$$

We specify right-to-left evaluation order for tuples, applied variant constructors, and :::

$$\begin{array}{c}
\frac{\vdash e \xrightarrow{L} e'}{\vdash e_1, \dots, e_m, e, v_1, \dots, v_n \xrightarrow{L} e_1, \dots, e_m, e', v_1, \dots, v_n} \quad \text{JR_expr_tuple_ctx} \\
\\
\frac{\vdash e_1, \dots, e_m, ((\% \text{primraise}) v), v_1, \dots, v_n \longrightarrow (\% \text{primraise}) v}{\vdash e \xrightarrow{L} e'} \quad \text{JR_expr_tuple_raise} \\
\\
\frac{\vdash constr(e_1, \dots, e_m, e, v_1, \dots, v_n) \xrightarrow{L} constr(e_1, \dots, e_m, e', v_1, \dots, v_n)}{\vdash constr(e_1, \dots, e_m, ((\% \text{primraise}) v), v_1, \dots, v_n) \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_constr_ctx} \\
\\
\frac{\vdash constr(e_1, \dots, e_m, ((\% \text{primraise}) v), v_1, \dots, v_n) \longrightarrow (\% \text{primraise}) v}{\vdash e_0 :: e \xrightarrow{L} e_0 :: e'} \quad \text{JR_expr_constr_raise} \\
\\
\frac{\vdash e \xrightarrow{L} e'}{\vdash e_0 :: e \xrightarrow{L} e_0 :: e'} \quad \text{JR_expr_cons_ctx1} \\
\\
\frac{\vdash e :: ((\% \text{primraise}) v) \longrightarrow (\% \text{primraise}) v}{\vdash e :: v \xrightarrow{L} e' :: v} \quad \text{JR_expr_cons_raise1} \\
\\
\frac{\vdash e \xrightarrow{L} e'}{\vdash e :: v \xrightarrow{L} e' :: v} \quad \text{JR_expr_cons_ctx2}
\end{array}$$

$$\frac{}{\vdash ((\% \text{primraise}) v) :: v' \longrightarrow (\% \text{primraise}) v} \text{JR_expr_cons_raise2}$$

We specify right-to-left evaluation for records. The bytecode implementation appears to go right to left after first reordering the record to correspond to the field ordering in the record type definition.

$$\frac{\frac{\frac{\vdash \{fn_1 = e_1; \dots; fn_m = e_m; \text{field_name} = expr; fn'_1 = v_1; \dots; fn'_n = v_n\} \xrightarrow{L} \{fn_1 = e_1; \dots; fn_m = e_m; \text{field_name} = expr'; fn'_1 = v_1; \dots; fn'_n = v_n\}}{\vdash \{fn_1 = e_1; \dots; fn_m = e_m; fn = (\% \text{primraise}) v; fn'_1 = v_1; \dots; fn'_n = v_n\} \longrightarrow (\% \text{primraise}) v} \text{JR_expr_record_raise}}{\vdash e \xrightarrow{L} e'} \text{JR_expr_record_ctx}}$$

The bytecode implementation appears to evaluate the leftmost position first in **with** expressions, so we follow that here.

$$\frac{\frac{\frac{\frac{\vdash \{v \text{ with } fn_1 = e_1; \dots; fn_m = e_m; \text{field_name} = e; fn'_1 = v_1; \dots; fn'_n = v_n\} \xrightarrow{L} \{v \text{ with } fn_1 = e_1; \dots; fn_m = e_m; \text{field_name} = e'; fn'_1 = v_1; \dots; fn'_n = v_n\}}{\vdash \{v' \text{ with } fn_1 = e_1; \dots; fn_m = e_m; fn = (\% \text{primraise}) v; fn'_1 = v_1; \dots; fn'_n = v_n\} \longrightarrow (\% \text{primraise}) v} \text{JR_expr_record_with_raise1}}{\vdash e \xrightarrow{L} e'} \text{JR_expr_record_with_ctx1}}$$

$$\frac{\vdash \{e \text{ with } field_name_1 = e_1; \dots; field_name_n = e_n\} \xrightarrow{L} \{e' \text{ with } field_name_1 = e_1; \dots; field_name_n = e_n\}}{\vdash \{(\% \text{primraise}) v \text{ with } field_name_1 = e_1; \dots; field_name_n = e_n\} \longrightarrow (\% \text{primraise}) v} \text{JR_expr_record_with_ctx2}$$

$$\frac{\frac{\vdash \{fn_1 = v_1; \dots; fn_m = v_m; field_name = v; fn'_1 = v'_1; \dots; fn'_n = v'_n\} \text{ with } field_name = v' \longrightarrow \{fn_1 = v_1; \dots; fn_m = v_m; field_name = v'; fn'_1 = v'_1; \dots; fn'_n = v'_n\} \text{ with } fn''_1 = v''_1; \dots; fn''_l = v''_l\}}{\vdash \{fn_1 = v_1; \dots; fn_m = v_m; field_name = v'; fn'_1 = v'_1; \dots; fn'_n = v'_n\} \text{ with } fn''_1 = v''_1; \dots; fn''_l = v''_l} \text{JR_expr_record_with_many}}$$

$$\frac{\vdash \{fn_1 = v_1; \dots; fn_m = v_m; field_name = v; fn'_1 = v'_1; \dots; fn'_n = v'_n\} \text{ with } field_name = v' \longrightarrow \{fn_1 = v_1; \dots; fn_m = v_m; field_name = v'; fn'_1 = v'_1; \dots; fn'_n = v'_n\}}{\vdash e \xrightarrow{L} e'} \text{JR_expr_record_with_1}$$

$$\frac{\vdash e \xrightarrow{L} e'}{\vdash e.\text{field_name} \xrightarrow{L} e'.\text{field_name}} \text{JR_expr_record_access_ctx}$$

$$\begin{array}{c}
\frac{\vdash ((\% \text{primraise}) v). \text{field_name} \longrightarrow (\% \text{primraise}) v}{\vdash ((\% \text{primraise}) v). \text{field_name} \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_record_access_raise} \\
\frac{\vdash \{fn_1 = v_1; \dots; fn_n = v_n; field_name = v; fn'_1 = v'_1; \dots; fn'_m = v'_m\}. \text{field_name} \longrightarrow v}{\vdash \{fn_1 = v_1; \dots; fn_n = v_n; field_name = v; fn'_1 = v'_1; \dots; fn'_m = v'_m\}. \text{field_name} \longrightarrow v} \quad \text{JR_expr_record_access} \\
\frac{\vdash e \xrightarrow{L} e'}{\vdash \text{assert } e \xrightarrow{L} \text{assert } e'} \quad \text{JR_expr_assert_ctx} \\
\frac{\vdash \text{assert } ((\% \text{primraise}) v) \longrightarrow (\% \text{primraise}) v}{\vdash \text{assert } ((\% \text{primraise}) v) \longrightarrow (\% \text{primraise}) v} \quad \text{JR_expr_assert_raise} \\
\frac{\vdash \text{assert true} \longrightarrow ()}{\vdash \text{assert true} \longrightarrow ()} \quad \text{JR_expr_assert_true} \\
\frac{\vdash \text{assert false} \longrightarrow (\% \text{primraise}) \text{Assert_failure}}{\vdash \text{assert false} \longrightarrow (\% \text{primraise}) \text{Assert_failure}} \quad \text{JR_expr_assert_false}
\end{array}$$

4.10 $\boxed{\vdash \langle \text{definitions}, \text{program} \rangle \xrightarrow{L} \langle \text{definitions}', \text{program}' \rangle}$ Definition sequence evaluation

Reduces a definition one-step. Type and exception definitions are moved into the tuple left sequence as encountered to support typing of intermediate states.

$$\begin{array}{c}
\frac{\vdash e \xrightarrow{L} e'}{\vdash \langle ds_value, \text{let } pat = e; ; \text{definitions} \rangle \xrightarrow{L} \langle ds_value, \text{let } pat = e'; ; \text{definitions} \rangle} \quad \text{Jdefn_let_ctx} \\
\frac{\vdash \langle ds_value, \text{let } pat = (\% \text{primraise}) v; ; \text{definitions} \rangle \longrightarrow \langle ds_value, (\% \text{primraise}) v \rangle}{\vdash v \text{ matches } pat \triangleright \{x_1 \leftarrow v_1, \dots, x_m \leftarrow v_m\}} \quad \text{Jdefn_let_raise} \\
\frac{\vdash \langle ds_value, \text{let } pat = v; ; \text{definitions} \rangle \longrightarrow \langle ds_value, \{x_1 \leftarrow \text{remv_tyvar } v_1, \dots, x_m \leftarrow \text{remv_tyvar } v_m\} ; \text{definitions} \rangle}{\vdash \neg(v \text{ matches } pat)} \quad \text{Jdefn_let_match} \\
\frac{\vdash \langle ds_value, \text{let } pat = v; ; \text{definitions} \rangle \longrightarrow \langle ds_value, (\% \text{primraise}) \text{Match_failure} \rangle}{\vdash \text{letrec_bindings} = (x_1 = \text{function pattern_matching}_1 \text{ and } \dots \text{ and } x_n = \text{function pattern_matching}_n) \quad \text{Jdefn_let_not_match}} \\
\frac{\vdash \text{recfun}(\text{letrec_bindings}, \text{pattern_matching}_1) \triangleright e_1 \dots \text{ recfun}(\text{letrec_bindings}, \text{pattern_matching}_n) \triangleright e_n}{\vdash \langle ds_value, \text{let rec letrec_bindings; ; definitions} \rangle \longrightarrow \langle ds_value, \{x_1 \leftarrow \text{remv_tyvar } e_1, \dots, x_n \leftarrow \text{remv_tyvar } e_n\} ; \text{definitions} \rangle} \quad \text{Jdefn_letrec} \\
\frac{\vdash \langle ds_value, \text{type_definition; ; definitions} \rangle \longrightarrow \langle ds_value; ; \text{type_definition}, \text{definitions} \rangle}{\vdash \langle ds_value, \text{exception_definition; ; definitions} \rangle \longrightarrow \langle ds_value; ; \text{exception_definition}, \text{definitions} \rangle} \quad \text{Jdefn_type} \\
\frac{\vdash \langle ds_value, \text{exception_definition; ; definitions} \rangle \longrightarrow \langle ds_value; ; \text{exception_definition}, \text{definitions} \rangle}{\vdash \langle ds_value, \text{exception_definition; ; definitions} \rangle \longrightarrow \langle ds_value; ; \text{exception_definition}, \text{definitions} \rangle} \quad \text{Jdefn_exn}
\end{array}$$

4.11 $\boxed{store(location) \triangleright expr}$ **Store lookup**

Gets the value stored at a given location.

$$\frac{\begin{array}{c} st(l) \triangleright e' \\ l \neq l' \\ \hline st, l' \mapsto e(l) \triangleright e' \end{array}}{st, l \mapsto e(l) \triangleright e} \text{ JSstlookup_rec}$$

4.12 $\boxed{\vdash store \xrightarrow{L} store'}$ **Store transition**

Coordinates a store with a label.

$$\frac{\begin{array}{c} \vdash st \longrightarrow st \quad \text{JRstore_empty} \\ \frac{st(l) \triangleright v}{\vdash st \xrightarrow{!l=v} st} \quad \text{JRstore_lookup} \\ \hline st'(l) \text{ unallocated} \end{array}}{\vdash st, l \mapsto expr, st' \xrightarrow{l:=v} st, l \mapsto \mathbf{remv_tyvar} v, st'} \text{ JRstore_assign}$$

$$\frac{st(l) \text{ unallocated}}{\vdash st \xrightarrow{\mathbf{ref}\ v=l} st, l \mapsto \mathbf{remv_tyvar} v} \text{ JRstore_alloc}$$

4.13 $\boxed{\vdash \langle definitions, program, store \rangle \longrightarrow \langle definitions', program', store' \rangle}$ **Top-level reduction**

The semantics of a machine is described as the parallel evolution of a structure body (the program) and a store. Each program evaluation step labelled L must be matched by a store evaluation step with the same label.

$$\frac{\vdash store \xrightarrow{L} store' \quad \vdash \langle definitions_value, program \rangle \xrightarrow{L} \langle definitions, program' \rangle}{\vdash \langle definitions_value, program, store \rangle \longrightarrow \langle definitions, program', store' \rangle} \text{ JRtop_defs}$$

4.14 $\vdash \text{expr behaves}$ Expression behaviour

This relation describes expressions whose behaviour is defined. This includes values, expressions that reduce, and raised exceptions. An expression with no behaviour is said to be stuck. In this definition of expression behaviour, we treat any reducing expression as behaving, no matter what (satisfiable) constraint is imposed on the label.

$$\frac{}{\vdash v \text{ behaves}} \text{ JRB_ebehaviour_value}$$

$$\frac{\vdash e \xrightarrow{L} e'}{\vdash e \text{ behaves}} \text{ JRB_ebehaviour_reduces}$$

$$\frac{}{\vdash (\% \text{primraise}) v \text{ behaves}} \text{ JRB_ebehaviour_raises}$$

4.15 $\vdash \langle \text{definitions}, \text{program}, \text{store} \rangle \text{behaves}$ structure body behaviour

As for expressions, a definition sequence behaves if it is a value, if it reduces (under any label), or if it raises an exception.

$$\frac{}{\vdash \langle \text{definitions_value}, , \text{store} \rangle \text{behaves}} \text{ JRB_behaviour_value}$$

$$\frac{\vdash \langle \text{definitions_value}, \text{program}, \text{store} \rangle \longrightarrow \langle \text{definitions}', \text{program}', \text{store}' \rangle}{\vdash \langle \text{definitions_value}, \text{program}, \text{store} \rangle \text{behaves}} \text{ JRB_behaviour_reduces}$$

$$\frac{}{\vdash \langle \text{definitions_value}, (\% \text{primraise}) v, \text{store} \rangle \text{behaves}} \text{ JRB_behaviour_raises}$$

5 Statistics

Definition rules:	310	good	0	bad
Definition rule clauses:	696	good	0	bad